



SAFETY DATA SHEET

BELZONA® 1111 (SUPER METAL) - BASE

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	BELZONA® 1111 (SUPER METAL) - BASE
INTERNAL ID	1004/0866/-/04
APPLICATION	Base component of a two component system. Mix with Solidifier component before use. Engineering grade repair system for repairing and rebuilding machinery and equipment. Application by plastic applicator or spatula provided. Please refer to the relevant Belzona® Instructions For Use for further information. For use only by professional operators.
SUPPLIER	Belzona Polymerics Limited Claro Road, Harrogate North Yorkshire HG1 4DS, England ☎ +44 (0) 1423 567641 +44 (0) 1423 505967 sds@belzona.com
EMERGENCY TELEPHONE	+44 (0) 1423 567641 (office hours)

2 HAZARDS IDENTIFICATION

Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION (1999/45) Xi;R36/38. R43. N;R51/53.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
EPOXY RESIN (Number average MW <= 700)	500-033-5	25068-38-6	10-30%	R43 Xi;R36/38 N;R51/53

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

INHALATION

Remove to fresh air. Keep the patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.

INGESTION

If accidentally swallowed obtain immediate medical attention. Keep at rest. Rinse mouth with plenty of water and drink plenty of water. Do NOT induce vomiting.

SKIN CONTACT

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners. If irritation or inflammation persists, seek medical attention.

EYE CONTACT

Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart, and seek medical advice.

5 FIRE-FIGHTING MEASURES

BELZONA® 1111 (SUPER METAL) - BASE

EXTINGUISHING MEDIA

Use: sand, alcohol resistant foam, carbon dioxide, chemical powder, water fog for larger fires.
Do NOT use water jet.

SPECIAL FIRE FIGHTING PROCEDURES

Fire will produce dense black smoke containing hazardous products of combustion (see Section 10). Exposure to decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or watercourses.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Avoid contact with skin and eyes. Refer to protective measures listed in Section 8.

ENVIRONMENTAL PRECAUTIONS

Prevent product entering drains or sewers. If the product enters drains or sewers in large quantities, the local Water Company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the appropriate National regulating agency. Refer to information sources listed in Section 16.

SPILL CLEAN UP METHODS

Scrape the majority of the product into a suitable labelled container. Cover the spill area with sand or other suitable inert material and sweep up into the container. Clean surfaces down with a water and detergent mixture. Refer to disposal methods listed in Section 13. Do not allow spilled product or the associated washings to enter surface water drains or watercourses.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

GENERAL

Vapours may collect in the container headspace during transit or prolonged storage. Avoid the inhalation of vapour when opening the container. Where possible open containers and mix components in a well ventilated place away from the application area. Avoid skin and eye contact. Smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection see Section 8. Always keep in containers made of the same material as the supply container. Good housekeeping methods and regular safe removal of waste materials should be observed. The Manual Handling Operations Regulations may apply to the handling of containers/packages of this product. Refer to the guide weight on the container/package when carrying out assessments.

FIRE/EXPLOSION

This product is combustible. Exclude sources of heat, sparks and open flame.

STORAGE PRECAUTIONS

Observe the label precautions. Store between 5°C and 30°C unless otherwise stated in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

ENVIRONMENTAL STORAGE PRECAUTIONS

Spillage, incorrect storage of chemicals or waste materials or unsuitable disposal activities can result in pollutants seeping through the soil, causing serious harm to groundwater- which is a vital source of drinking water. All wastes especially liquid wastes, must be securely stored on site in designated areas that are isolated from surface drains and banded to contain any spillages.

STORAGE CLASS

The principals contained in the HSE guidance note Chemical Warehousing: storage of packaged dangerous substances (HSG71) should be observed when storing this product.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT COMMENTS

When personal protective equipment, including respiratory protective equipment, is used to control exposure to hazardous substances it must be selected to meet the requirements of the COSHH Regulations.

ENGINEERING MEASURES

Open containers in a well ventilated area.

RESPIRATORY EQUIPMENT

Respiratory protection is not normally required but it may be required when this product is used in confined spaces or where adequate ventilation cannot be achieved.

BELZONA® 1111 (SUPER METAL) - BASE

HAND PROTECTION

GENERAL GUIDANCE ON HAND PROTECTION

Hand protection should be selected in accordance with EN 374 Protective gloves against chemicals. The breakthrough time of the gloves selected should exceed the expected use period. Where this is not possible gloves should be changed in good time, and in any case before the breakthrough time is exceeded. If any doubt exists, advice should be sought from glove suppliers on appropriate types. Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred.

SPECIFIC RECOMMENDATIONS

Use protective gloves made of: Neoprene. Nitrile.

STANDARD APPLICATIONS

Medium-heavy weight gauntlet type gloves that provide wrist protection are suitable.

EMERGENCY REPAIRS OR APPLICATION OF SINGLE UNITS

Light weight disposable gloves are normally suitable.

EYE PROTECTION

It is recommended that eye protection, for example safety spectacles or goggles are worn at all times during the handling and use of this material. Eye protection should be selected in accordance with EN 166 Personal eye protection. During subsequent machining, grinding, abrasion or removal of this product appropriate eye protection should be selected according to the type of tools or equipment used.

OTHER PROTECTION

STANDARD APPLICATIONS

Synthetic polyethylene coveralls such as the Tyvek PRO-TECH® or equivalent coveralls manufactured to EN 13034 Type 6, Protective clothing against liquid chemicals. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.

EMERGENCY REPAIRS OR APPLICATION OF SINGLE UNITS

Cotton overalls are normally suitable.

HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Ensure eye wash facilities (fountain, bottle, vials, etc.) are readily available. Do not put contaminated articles or equipment e.g. spatulas, applicators, brushes, cloths etc., into pockets. Where necessary, contaminated work clothing should be removed to prevent cross contamination of surfaces and the risk of inadvertent skin contact and ingestion.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Paste.		
COLOUR	Dark grey.		
ODOUR	Epoxy.		
PHYSICAL DATA COMMENTS	This section contains typical values for Health, Safety and Environmental guidance only and is not intended to represent a technical specification for the product. L = Low. NIA = No Information available. LP = See Section 12. N.ap = Not Applicable.		
SOLUBILITY	Immiscible with water		
BOILING POINT (°C)	> 200 @ 760 mm Hg	RELATIVE DENSITY	2.70 - 2.90 @ 20 °C
VAPOUR DENSITY (air=1)	>1	VAPOUR PRESSURE	L
pH-VALUE, CONC. SOLUTION	NIA	VISCOSITY	N.ap
DECOMPOSITION TEMPERATURE (°C)	> 200	FLASH POINT (°C)	> 170 CC (Closed cup).
AUTO IGNITION TEMPERATURE (°C)	>300	PARTITION COEFFICIENT (N-Octanol/Water)	LP

10 STABILITY AND REACTIVITY

STABILITY

Stable under recommended storage and handling conditions (see Section 7). In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide may be produced.

CONDITIONS TO AVOID

Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction.

11 TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION

There is no data on the product itself. Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitizer and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and to sensitisation with possibly cross-sensitisation to other epoxies.

BELZONA® 1111 (SUPER METAL) - BASE

INHALATION

Vapours that may collect in the container headspace during transit or prolonged storage may be harmful by inhalation.

INGESTION

Ingestion is not normally an exposure risk arising from professional applications. Inadvertent ingestion of small amounts of this product through poor hygiene or cross contamination may cause irritation of mucous membranes.

SKIN CONTACT

Prolonged or repeated contact with the skin may cause irritation, blistering or dermatitis. Causes of allergic skin reaction have been observed. May cause sensitisation by skin contact.

EYE CONTACT

May cause eye irritation.

ROUTE OF ENTRY

Skin and/or eye contact. Ingestion. Inhalation.

MEDICAL SYMPTOMS

Prolonged or repeated contact with the skin or mucous membrane may result in irritant symptoms such as redness, blistering or dermatitis. Onset of symptoms may be delayed.

MEDICAL CONSIDERATIONS

Skin contact constitutes a pronounced hazard. Persons with a history of skin sensitisation problems should only be employed in processes in which this product is used under appropriate medical supervision.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

There is no data on the product itself. The following information is provided on the basis of the individual component data available, and in strict compliance with the conventional classification guidelines for preparations as outlined in the Chemicals (Hazard Information and Packaging for Supply) Regulations. The product should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface waters. See also Sections 5, 6, 7, 9 and 13.

BIOACCUMULATION

Based on the epoxy resin (number average MW≤700) content, this product is expected to bioaccumulate. Log octanol/water partition coefficient (Log Pow) is expected to be greater than 3.0. May cause long-term adverse effects in the aquatic environment.

DEGRADABILITY

Based on the epoxy resin (number average MW≤700) content, this product is not expected to be readily biodegradable according to OECD/EC guidelines. May cause long-term adverse effects in the aquatic environment.

ACUTE FISH TOXICITY

Based on the epoxy resin (number average MW ≤700) content, this product is expected to have experimental LC50/EC50/IC50 values between 1 and 10 mg/l in most sensitive species. Toxic to aquatic organisms.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

All cleaning activities including cleaning of equipment, floors and containers, can produce large volumes of contaminated waste. All cleaning agents used are potentially polluting. Water containing detergents, degreasers or any other cleaning agents must not be allowed to enter the surface water drains or soakaways. All water based cleaning/degreasing operations should be carried out in designated areas away from the surface water system and drained to the foul water system. Where this is not possible the surface water system should be isolated by suitable damming techniques and the contaminated water collected and removed for controlled safe disposal. Where water immiscible cleaners/degreasers are used for example solvents, the relevant product safety data sheet should be referred to for information on safe disposal.

DISPOSAL METHODS

GENERAL

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Controlled wastes include non-hazardous industrial and hazardous chemical wastes. All controlled wastes should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act. In addition, hazardous chemical wastes should be disposed of in accordance with the Hazardous Waste Regulations. When in doubt, using information provided in this safety data sheet, advice should be obtained from the National regulating agency whether the Hazardous Waste Regulations apply. Refer to information sources listed in Section 16.

COMPONENT DISPOSAL

TRANSIT PACKAGING: shrink or stretch wrap, boxes and fittings that have not been contaminated with product should be re-used or recycled. UNREACTED PRODUCT: and empty uncleaned containers should be disposed of as controlled wastes. REACTED PRODUCT: contaminated mixing boards, spatulas, applicators, brushes, nominally empty containers and mixing bowls- once fully cured- should be disposed of as non-hazardous chemical waste.

BELZONA® 1111 (SUPER METAL) - BASE

WASTE CLASS

European Waste Catalogue (EWC) code: 08 04 09

The EWC code quoted in this section is a general entry. EWC codes should be assigned based on the end use of the product. Where a more specific code is available it should be used in preference to the code given above. Where in doubt refer to the List of Wastes, your local licensed waste contractor or the National regulating agency. Refer to information sources listed in Section 16.

14 TRANSPORT INFORMATION

GENERAL

Transport classification: labelling and packaging requirements may vary with pack and load size. Please refer to the current transport regulations.

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage.

PROPER SHIPPING NAME

Environmentally hazardous substance, solid, n.o.s. (containing Epoxy resin mixture)

ROAD TRANSPORT NOTES

Transport category 3

UN NO. ROAD	3077	ADR CLASS NO.	9
ADR PACK GROUP	III	UN NO. SEA	3077
IMDG CLASS	9	IMDG PACK GR.	III
MARINE POLLUTANT	No.	UN NO. AIR	3077
AIR CLASS	9	AIR PACK GR.	III

15 REGULATORY INFORMATION

LABELLING



Irritant



Dangerous for the environment

CONTAINS

EPOXY RESIN (Number average MW <= 700)

RISK PHRASES

R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

P5	Contains epoxy constituents. See information supplied by the manufacturer.
S36/37	Wear suitable protective clothing and gloves.
S60	This material and its container must be disposed of as hazardous waste.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.

UK REGULATORY REFERENCES

This product is classified and labelled for supply in accordance with the Chemicals (Hazard Information and Packaging for Supply) Regulations 2002, as amended.

The provisions of the Health and Safety at Work Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

The information contained within this safety data sheet is provided in accordance with Regulation (EC) No. 1907/2006 as amended concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

ENVIRONMENTAL LISTING

The Environmental Protection Act 1990.

The Environment Act 1985.

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC.

BELZONA® 1111 (SUPER METAL) - BASE

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging for Supply) Regulations 2002, as amended (SI 2002: 1689).
Control of Substances Hazardous to Health Regulations 2002, as amended (SI 2002: 2677).
Provision and Use of Personal Protective Equipment Regulations 1992 (SI 1992: 2932).
The Confined Spaces Regulations 1997 (SI1997: 1713).
Special Waste Regulations 1996 (SI 1996: 972), as amended (Scotland Only).
The Hazardous Waste Regulations 2005 (SI2005: 894), as amended.
The List of Wastes Regulations 2005 (SI2005: 895), as amended.

APPROVED CODE OF PRACTICE

Control of Substances Hazardous to Health (Fifth edition) approved code of practice and guidance.

GUIDANCE NOTES

PPG11: Preventing pollution at industrial sites.
PPG18: Control of Spillages and fire fighting run-off.
HSG97 A step by step guide to COSHH assessment.
HSG193 COSHH essentials: easy steps to control chemicals.
HSG53 The selection, use and maintenance of respiratory protective equipment.
Working with ADR: An introduction to the carriage of dangerous goods by road.
Hazardous Waste: Interpretation of the Definition and Classification of Hazardous Waste (Technical Guidance WM2).

16 OTHER INFORMATION

GENERAL INFORMATION

The information contained within this safety data sheet does not constitute the users own assessment of workplace risks as required by other health and safety legislation. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant National legislation are complied with. The information contained within this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

RESTRICTIONS ON USE

The product should not be used for purposes other than those recommended and in addition should be applied in line with the procedures detailed in the related Instructions For Use (IFU) leaflet.

This product may only be used in 'confined spaces' where a suitable and sufficient assessment has been carried out by a competent person in accordance with the Confined Spaces Regulations. The assessment should cover the risks involved for all work activities.

INFORMATION SOURCES

Health Surveillance at Work (HSG61) available from HSE Books.

UK ENVIRONMENTAL REGULATING AGENCIES: England and Wales- Environment Agency; Scotland- Scottish Environment Protection Agency (SEPA); Northern Ireland- Environment and Heritage Service.

REVISION COMMENTS

REVISION. This safety data sheet has been revised in the following Section(s): 16, Please observe the REVISION DATE. Should you be reading a safety data sheet that is more than 24 months old or have concerns over its validity, please contact your local Belzona consultant or Belzona direct (sds@belzona.com) and the most current information will be sent to you.

REVISION DATE 04-01-2011

SAFETY DATA SHEET STATUS

Approved.

RISK PHRASES IN FULL

R36/38 Irritating to eyes and skin. , R43 May cause sensitisation by skin contact. , R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

REVISION NO. 4.7