

## A 130 Paste

### Metal free anti seize paste for high loads and temperatures

#### Product description

Synthetic oil and metal free solid lubricants paste for assembly of bolted connections, sliding contact surfaces and press-fit joints

#### Features & benefits

- Service temperature range of -40°C to +1500°C
- Makes disassembly easy and non-destructive even after long operational periods at high temperatures and adverse working environments
- High load withstanding capacity and creates an effective matrix between mating surfaces to prevent metal-to-metal contact
- Free from any ingredients that can cause metal brittleness
- Good corrosion protection
- Coefficient of friction is similar to that of oiled bolts to help calculate tightening torque
- Prevents bolt breaking, sintering, fusion, seizure, thread stripping and distortion of threads, stress cracking
- Low coefficient of friction

#### Applications

- For threaded and flanged connections operating at very high temperatures and corrosive conditions to enable faster and rapid non-destructive disassembly after extended operational periods
- Use for press fit joints, guides, sliding contact surfaces, door hinges, seals, spark plugs, springs.

#### How to use

Use as supplied. Never mix with other greases or dilute with any oils. For optimum performance, clean the contact surface.

Use any ASV heavy duty industrial strength solvent based cleaner degreaser available in aerosol spray or bulk liquid pack. When using a water based degreaser, ensure complete removal of any residues of the water based alkaline cleaning solution prior to applying grease.

Apply on clean, dry, degreased contact points by brush, cloth or chamois leather. Rub intensively on the metal surface to form a thin uniform lubricating film.

All ASV® pastes are high concentrations of solid lubricants in suitable oil carriers. Oil separation might occur over an extended period of time. If required, stir the contents by any simple mechanical means for a few minutes, and the product will regain its original consistency. Never use in excess as is customary with grease lubrication and never use paste instead of grease.

Test	Unit	Result	Standard
Appearance		Solid, grease	Visual
Colour		Gray black	Visual
Base oil		Synthetic	Visual
Thickener		Inorganic	In house
Penetration (unworked)	mm/10	280-310	ASTM D-217
NLGI Class		1	DIN 51 818
Density @ 20°C	g/cm <sup>3</sup>	1.21	ASTM D-1298
Drop point	°C	None	ASTM D-566
Lower operating temperature	°C	-40	In house
Upper operating temperature*	°C	+1500	In house
Four ball OK weld load	N	4800	DIN 51 350 pt.4
Copper strip corrosion		1a	ASTM D-4048
SKF Emcor test	corr. degree	2	DIN 51 802
Coverage	m <sup>2</sup> /kg	3-4	
Shelf life from manufacturing month, unopened container	Months	60	In house

\* thermal resistance of lubricating solids

## General

Use in well-ventilated areas. Avoid continuous breathing of vapor and spray mist. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

## Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards.

Manufactured by:  
ASV Multichemie Private Limited  
E 14, Additional MIDC, Patalganga  
Panvel-410 220 INDIA



[WWW.ASVMULTICHEMIE.COM](http://WWW.ASVMULTICHEMIE.COM)

## Disposal

All used and unused product should be disposed of in accordance with state regulations.

## Limited warranty

Product manufactured is for industrial use only. The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK®  
SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV  
MULTICHEMIE PRIVATE LIMITED, INDIA