

CS 90 Spray

Carbon Remover

Product description

- Solvent based formulation

Applications

- For removal of carbon, paint, adhesives, lacquers and varnishes without excessive scraping or causing damage to the surfaces
- For cleaning stubborn grease, oil, varnish, carbon deposits

Features & benefits

- Removes carbon, paints, varnishes
- Fast acting formula cleans dried grease & oil
- Protects surface finish from excessive scraping

How to use

Mask areas not requiring removal or for protection from overspray. Observe precautions of wearing protective eyewear and hand gloves while handling this product. Spray liberally over surface and allow solvents 5-10 minutes to work for softening paint and then remove with a putty knife or cloth rag. For stubborn or thick coatings, repeat the same procedure. To prevent clogging of actuator and valve dip-tube after use, invert the can and press the actuator button for a short burst till only clear propellant gas comes out.

Caution

Contains flammable solvents and propellant. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.

Test	Unit	Result
Appearance		Hydrocarbon gas propelled liquid
Description		Cleaner / Degreaser
Colour		Whitish to colourless
Odor		Solvent
Film type		Thick, foamy
Specific gravity concentrate	g/cm ³	0.88-0.92
ISO VG grade		N/A
Evaporation rate		N/A
KB value		N/A
Dielectric strength		N/A
Plastic safe		No
Service temperature range	°C	N/A
Flash point	°C	-25°C (closed cup) aerosol
Flammability class		Extremely flammable
Film thickness	Mils	N/A
Dry time, full dry	h	N/A
Dry time, tack free	h	N/A
Recoat	h	N/A
Method of removal		N/A
Four ball weld load	N	N/A
Four ball wear	mm	N/A
NSF category code		N/A
NSF number		N/A
Solubility in water		No
Coverage	m ² /can	N/A
Propellant		Hydrocarbon
Shelf life	months	36 from date of manufacture

N/A: not applicable

General

Use in well-ventilated areas. Avoid continuous breathing of vapor and spray mist. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards.

Manufactured by:
ASV Multichemie Private Limited
E 14, Additional MIDC, Patalganga
Panvel-410 220 INDIA



WWW.ASVMULTICHEMIE.COM

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Limited warranty

Product manufactured is for industrial use only. The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK®
SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV
MULTICHEMIE PRIVATE LIMITED, INDIA