



#### Applications

Cleaning & freeing:  
Auto Chokes  
Carburetor Elements  
Linkages  
Intake Parts  
PCV Systems

## Carb Cleaner

ASV® Carb Clean is a blend of powerful cleaning solvents specifically designed to clean, dissolve and remove performance inhibiting residues like gum, dirt, dust, sludge and varnish deposits that tend to build up on carburetors, heat valves and automatic chokes, throttle plates, PCV valves and linkages.

It helps clean and free sticky valves, heat risers and throttle linkages.

Effective cleaning and removal of contaminants maximizes carburetor performance while improving fuel system efficiency thereby ensuring and maximizing fuel economy.

Appearance	Color	Type	Flash Point, °C	Specific Gravity, Active Contents	Evaporation Rate	Residue On Evaporation	Propellant
Clear Liquid	Colorless	Non chlorinated	<-17C	~0.80 g/cc	Very Fast	None	Carbon Dioxide

#### Available Packaging

- 500 ml aerosol spray

#### Shelf Life

24 months from date of  
manufacture in sealed condition



#### Directions for use

Keep away from electrical connections and battery terminals. CAUTION Extremely flammable. Do not use on hot engine surface. IMPORTANT Do not spray or spill on painted surfaces. Protect from product overspray. Attach extension tube for pin point application. For cleaning Carburetor and Linkage, with engine off and cool, remove air cleaner and spray carburetor throat and other interior and exterior parts. Allow carburetor to dry completely. With engine running, spray ASV® Carb Cleaner down the carburetor throat to remove deposits from throttle plate area. For cleaning Automatic Chokes, turn off the engine, repeatedly open and close the choke manually and spray on both ends and linkages of the choke valve. For cleaning Manifold Heat Control Valve, with engine off and cold, spray ASV® Carb Cleaner on exposed ends of cool heat riser shaft. Allow cleaning agents to penetrate and clean. Move counterweight until free. For cleaning PCV Valves, disassemble crank case side of valve and with engine running spray ASV® Carb Cleaner into the open end of the valve while working the plunger back and forth. Does not contain lead or silicone. Will not harm catalytic converters, oxygen sensors or fuel injectors.

**Caution:** Contents under pressure. Do not puncture, pierce or incinerate the container, even after use. Protect from sunlight and store away from heat and sources of ignition. Do not use on energized equipment or on live circuits. Do not expose to temperatures exceeding 50°C (120°F). Use only in well ventilated areas. As this can conduct electricity, prevent the risk of electrical shock by keeping away from all live electrical connections and sources of electricity. Do not breathe vapors or spray mist. Harmful by inhalation and avoid contact with skin and eyes. In case of eye contact, flush eyes with water and contact a physician. If swallowed, may be harmful or fatal. DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY. KEEP OUT OF REACH OF CHILDREN. Dispose as industrial waste only in accordance with governing regulations. For proper disposal empty aerosol can completely.

#### General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

#### Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safety, short and long term exposure, physical and health hazards and is available from ASV or your local ASV distributor.

#### Disposal

All used and unused product should be disposed of in accordance with state regulations.

#### Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV® product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV® is a leading pioneer in the production of specialized lubricants and technical chemicals in India for the MRO industry for nearly 5 decades.

Founded in 1969 with the introduction of Molysulf® line of solid film lubricants for tribological applications, today ASV® manufactures a broad range of products for diversified industrial needs as lubrication, cleaning and protection by way of performance oriented cost benefitting solutions.

Contact us today to discover how you can increase productivity as well as increase equipment performance while reducing maintenance and operational costs.

# MOLYSULF®

[www.asvmultichemie.com](http://www.asvmultichemie.com)

#### ASV MULTICHEMIE PRIVATE LIMITED

Registered Office & Works : W 46, TTC Industrial Area, MIDC Rabale, Navi Mumbai-400 701, INDIA  
Tel: +91 (022) 2764 2514 | E-mail: [info@asvmultichemie.com](mailto:info@asvmultichemie.com)  
MOLYSULF® & ASV® Specialty Lubricants & MRO Technical Chemicals  
© Registered trademark of ASV Multichemie Private Limited, INDIA