



Yeşilbayır Mah. Şimşir Sk. No: 22 Hadımköy - İstanbul/TÜRKİYE. Tel: 0212 771 13 71 Fax: 0212 771 38 88 🍃 www.akfix.com - info@akfix.com

# **AKFIX E60 ELECTRICAL CONTACT SPRAY**

## **1 – DESCRIPTION**

AKFIX E60 ELECTRICAL CONTACT SPREY is a product designed to remove flux and other surface contaminants. The product evaporates quickly from the surface without leaving any residue. It is designed for cleaning grease, dirt, oil etc. from electric-electronic equipment.

# **2 – PROPERTIES**

- Fast cleaning action for removal of flux traces, light oils, finger prints and other contaminants. •
- Periodic planned application prolongs the life expectancy of components. •
- Non-conductive and non-corrosive.
- Evaporates completely, leaving no residue. •
- Safe for all metal surfaces, most rubbers, plastics and coatings. It is recommended to be tested • on sensitive plastics, adhesive-mounted or stressed parts.
- Convenient to use 360° (upside-down). •

## **3 – APPLICATION AREAS**

- Calculators
- Computers •
- Digital Equipment •
- **Electronic Ignitions** •
- Navigation Equipment •
- Printed Circuits •
- Radars •
- Radios .
- Switches and Relays •
- **Circuit breakers** •
- Alarm and signal systems •
- Terminals •
- Plugs and sockets

#### **4-INSTRUCTIONS**

Akfix before applying electro contact cleaner, disconnect electric devices from the power line and wait for some minutes until there is no more electric tension inside the machine. Spray a sufficient quantity onto the parts to be cleaned from a distance of 25-30 cm. Electrical Contact Spray evaporates very quickly and does not leave any residues. Wiping or brushing supports the cleaning effect. Devices should be switched on only when both propellant and active subtance have evaporated completely.





Yeşilbayır Mah. Şimşir Sk. No: 22 Hadımköy - İstanbul/TÜRKİYE Tel: 0212 771 13 71 Fax: 0212 771 38 88 🔉 www.akfix.com - info@akfix.com

# **5- PACKAGING**

Product	Volume	Package
E60	200 ml	12
E60	400 ml	24

# **6- STORAGE**

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 28°C (46° and 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

# **7- RECTRICTIONS**

- Pressurized container. •
- Keep away from direct sunlight. •
- Keep away from sources of ignition. ٠
- Use only in well-ventilated areas. •
- Keep out of reach of children. •

## **8- TECHNICAL PROPERTIES**

Form	: Aerosol
Appearance	: Clear colorless liquid
Specific gravity	: 0,802
Color	: Colorless
Odor	: Solvent
Shelf Life	: 24 months
VOC	: %55