

Technical Information

NF Multi Lube

Multipurpose, Multifunctional 5-in-1 Lubricant Non Flammable Grade

Product Description

ASV[®] NF Multi Lube is a fast acting industrial grade lubricant, rust penetrant and corrosion inhibitor. It forms a clear thin non-drying lubricating film that penetrates deep into the minutest crevices to displace trapped moisture and leaves behind a protective film to seal out further moisture and corrosion. Its unique low surface tension formula rapidly attacks rust to free seized or frozen components. It is nonconductive, non-staining and offers complete protection to metal surfaces indoors as a medium term corrosion inhibitor for protection against corrosion and moisture penetration for up to 12 months under normal storage conditions.

ASV[®] NF Multi Lube does not contain any silicones, ozone depleting chemicals, CFC's or harmful chlorinated solvents and is safe for use on around all metals, plastics, rubbers and other industrial finishes.

Benefits

- Multifunctional formula lubricates all sliding and moving parts with a long lasting thin oily lubricating film
- Rapidly penetrates minute cracks and pores to displace trapped moisture
- Penetrates deeply through rust to loosen scale and corroded or frozen parts
- Leaves a thin, long lasting film, film to prevent formation of rust or corrosion
- Cleans & removes oils, greases and other light contaminants
- Provides greaseless, non staining, silicone free lubrication and protection

Applications

A product as versatile as this has hundreds of multipurpose uses in all types of industrial, marine, aviation, electrical / electronic, electromechanical, commercial and domestic applications.

- <u>Lubrication</u>: Thin, non-drying protective oily film effectively lubricates moving parts as tuners, micro switches, power tools, automation equipment, locks, vending machines.
- <u>Rust Penetration</u>: For rapidly loosening tight, rusted or frozen components with high penetrating action.
- <u>Moisture Displacement</u>: Rapidly dries wet ignitions & removes trapped moisture from electrical / electronic systems.
- <u>Corrosion Protection</u>: For dies, jigs, tools, relays, connectors, switches, instruments, finished welds, casings, shafts, motors, freshly machined surfaces.
- <u>Cleaner</u>: For dissolving and removing grease, oil and other light contaminants.
- Prevention: Of entry of further moisture.

Directions for Use (Aerosol)

For rust penetration, spray liberally onto the surface. Allow solvents to penetrate and free rusted parts. Period for penetration may vary depending upon the length of time the product has been rusted for and in some cases may even take up to hours. Use an absorbent rag or a brush to remove dirt, rust, scales & dust. For lubrication, spray lightly and evenly over surface area to be lubricated. For moisture displacement, spray until clear product comes out and emulsified residue is totally clear. For metal protection, spray liberally and do not wipe off protective film from the surface. **Caution:** Use with adequate ventilation.

Technical Information

NF Multi Lube

Multipurpose, Multifunctional 5-in-1 Lubricant, Non Flammable Grade

Technical Properties

Property*		Aerosol
Appearance	Visual	Liquid
Color	Visual	Amber brown
Odor		Mild sweetish
Specific Gravity @ 27°C	In house	Above 1.00
Viscosity @ 40°C	ASTM D 445	3-4 cst
Flash Point (solvent)	ASTM D 92	None
Type Of Film	Visual	Non drying oily
Film Thickness	In house	0.02-0.05 mm
Propellant		Non flammable CO2
* of active ingredients		

Available Packaging

- 400 ml / 525 g aerosol can

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Shelf Life

12 months from date of manufacture in sealed condition

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV[®] product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV MULTICHEMIE PRIVATE LIMITED

Registered Office: 327, Arun Chambers, Tardeo Road, Tardeo, Mumbai-400 034, INDIA Tel: +91 (022) 2764 2514 I Fax: +91 (022) 2352 6318 I E-mail: info@asvmultichemie.com MOLYSULF® & ASV® Specialty Lubricants & MRO Technical Chemicals. ® Registered trademark of ASV Multichemie Private Limited, INDIA. THIS PRODUCT IS DEVELOPED AND MANUFACTURED BY US FOR INDUSTRIAL USE ONLY.

Page 2 of 2

Distributed by: