

مؤسسة تقنية الانسياب للتجارة | Technical Beacons For Trading Est.

لتموين المواد الصناعية | For Industrial Materials Supply

الرقام الضريبي VAT Reg. No. 302060012400003 س.ت C.R:4030349684



Acetone

Product Specification - Version 10a dated 7/31/14

Specifications	Minimum	Maximum	Test Method
Purity (wt% - wet basis)	99.5		GC
Specific Gravity @ 20/20C	0.7910	0.7930	ASTM D4052
Water (wt%)		0.5	ASTM D1364
Acidity as Acetic Acid (wt%)		0.002	ASTM D1613
Alkalinity as NH3 (wt%)		0.001	ASTM D1614
Color (Pt-Co)		5	ASTM D5386/D1209
Distillation Range (degrees C)	1C including 56.1C		ASTM D1078
Permanganate Stability (mins@25C)	120		ASTM D1363
Residue on Evaporation (mg/100ml)		2	ASTM D1353
Benzene (mg/kg)	10		GC
Miscibility with DIW	No Opalescence		ASTM D1722
Appearance	Clear and bright		ASTM E2680

Notes: Typical product at manufacture satisfies ASTM D329-07 test criteria.

Reason for revision:

Version 8a dated 11/15/12 GAT - Appearance E2680 Version 9a dated 11/5/13 GAT - Purity wet basis, Color D5386/D1209 Version 10a dated 7/31/14 GAT - Sasol Chemicals (USA) LLC

Sasol Chemicals (USA) LLC

900 Threadneedle, Suite 100 Houston, TX 77079 Telephone: (+1) 281 588 3000 www.sasol.com

> n Kingdom of Saudi Arabia - P.O.Box 65417 Jeddan 21556 **a** +966 12 642 2266 info@tech-beac.com \times # +966 54 400 9844

www.tech-beac.com alam@tech-beac.com

اليبان 109 BAN# SA52 1000 001 218 216 5000 109 حسابنا في البنك الاهلي التجاري - BAN# SA52 1000 001 218 216 5000 Al-Suhaifa District Old Makkah Road Kilo 1 Bab Makkah , Jeddah Saudi Arabia

جدة المملكة العربية السعودية كة القديم حيفة - باب مكة كيلو ١ طريق