

## Wire Rope & Gear Lube Spray

### Heavy duty grease with MoS<sub>2</sub> solid lubricant

#### Product description

- Extreme pressure grease for high performance lubrication

#### Applications

On open gears, wire ropes and steel cables in all cranes, ships, hoists, and elevators especially exposed to marine environment or under adverse operating conditions.

#### Features & benefits

- Protect against heavy loads, galling, and seizing
- Molybdenum disulfide solid lubricant & EP additives withstand high loads and pressures
- Reduces wear and friction
- Resists vibratory shocks
- Does not break down or melt or fling under prolonged use
- Effectively provides lubrication & corrosion protection even to the innermost strands

#### How to use

Shake can vigorously for a couple of minutes before spraying till bearing noise from inside the container is audible. Repeat before every application. Spray on clean, dry and degreased surfaces in thin light coats. Allow the solvents to evaporate. Spray from a distance of 20-30 cm.

#### Caution

Contains flammable propellant and solvents. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.

Test	Unit	Result
Appearance		Hydrocarbon gas propelled liquid
Description		Lubricant
Colour		Black
Odor		Mild petroleum
Film type		Oily
Specific gravity concentrate	g/cm <sup>3</sup>	0.67-0.69
ISO VG grade		N/A
Evaporation rate		N/A
KB value		N/A
Dielectric strength		N/A
Plastic safe		N/A
Service temperature range	°C	N/A
Flash point	°C	-25°C (closed cup) aerosol
Flammability class		Extremely flammable
Film thickness	Mils	N/A
Dry time, full dry	h	N/A
Dry time, tack free	h	N/A
Recoat	h	N/A
Method of removal		N/A
Four ball weld load	N	N/A
Four ball wear	mm	N/A
NSF category code		N/A
NSF number		N/A
Solubility in water		No
Coverage	m <sup>2</sup> /can	N/A
Propellant		Hydrocarbon
Shelf life	months	36 from date of manufacture

N/A: not applicable

## General

Use in well-ventilated areas. Avoid continuous breathing of vapor and spray mist. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

## Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards.

Manufactured by:  
ASV Multichemie Private Limited  
E 14, Additional MIDC, Patalganga  
Panvel-410 220 INDIA



**WWW.ASVMULTICHEMIE.COM**

## Disposal

All used and unused product should be disposed of in accordance with state regulations.

## Limited warranty

Product manufactured is for industrial use only. The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK®  
SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV  
MULTICHEMIE PRIVATE LIMITED, INDIA