

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 1 of 12

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part A

SECTION 1: Identification

Product identifier

Product name: Epoxy Putty Stick - Steel - Part A

Product code: 8267AUS



Recommended use of the product and restriction on use

Relevant identified uses: Not determined or not applicable.

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

J-B Weld Company, LLC
400 CMH Road
Sulphur Springs, TX 75482
903-885-7696

Supplier:

Australia

HPP Lunds
1/195 Jackson Rd
Sunnybank Hills, Qld 4109
1300-306-781

Emergency telephone number:

Australia

InfoTrac

1300-366-961 (24 hours)

SECTION 2: Hazard(s) identification

GHS classification:

Skin irritation, category 2

Eye irritation, category 2A

Skin sensitization, category 1

Label elements

Hazard pictograms:



Signal word: Warning

Hazard statements:

H315 Causes skin irritation

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

Precautionary statements:

P264 Wash hands thoroughly after handling

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray

P272 Contaminated work clothing should not be allowed out of the workplace

P280 Wear face protection

P321 Specific treatment (see supplemental first aid instruction on this label)

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 2 of 12

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part A

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P362 Take off contaminated clothing and wash before reuse

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337+P313 If eye irritation persists: Get medical advice/attention

P501 Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified:

None

SECTION 3: Composition and information on ingredients

Identification	Name	Weight %
CAS number: 25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	10-30
CAS number: 3101-60-8	P-tert-butyl(phenyl 1-(2,3-epoxy)propyl ether	<2
CAS number: 14807-96-6	Talc (non asbestiform)	30-60
CAS number: 65997-17-3	Glass, oxide, chemicals	10-30
CAS number: 13463-67-7	Titanium Dioxide	<1

Additional Information:

CAS # 65997-17-3 is classified as a carcinogen in its inhalable form. Since the fiberglass powder in this product is not inhalable, the product itself is not classified as a carcinogen in the form presented.

SECTION 4: First aid measures

Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance.

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After eye contact:

Rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 3 of 12

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part A

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Treat symptomatically.

SECTION 5: Fire fighting measures

Extinguishing media

Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable extinguishing media:

Do not use water jet.

Specific hazards during fire-fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 4 of 12

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part A

Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and storage precautions

Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure controls and personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Australia	Talc (non asbestiform)	14807-96-6	TWA: 2.5 mg/m ³ (containing no asbestos fibers)
	Glass, oxide, chemicals	65997-17-3	TWA: 0.5 fibers/ml (of air [Superfine glass fiber])
	Glass, oxide, chemicals	65997-17-3	TWA: 0.5 fibers/ml (of air [Synthetic mineral fibers])
	Glass, oxide, chemicals	65997-17-3	TWA: 0.5 fibers/ml (of air [Glasswool including superfine glass fiber])
	Glass, oxide, chemicals	65997-17-3	TWA: 0.5 fibers/ml (of air [Rockwool])
	Glass, oxide, chemicals	65997-17-3	TWA: 0.5 fibers/ml (of air [Ceramic fibers])
	Titanium Dioxide	13463-67-7	TWA: 10 mg/m ³ (National Workplace OELs)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Not determined or not applicable.

Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 5 of 12

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part A

handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal protection equipment

Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Very thick black paste (solid)
Odor	Not determined or not available.
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	135 °C (275 °F)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	2.15
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 6 of 12

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part A

Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

SECTION 10: Stability and reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible materials:

None known.

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Hazard information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	oral	LD50 Rat: > 2000 mg/kg
P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	oral	LD50 Rat: > 2000 mg/kg
	dermal	LD50 Rat: > 2000 mg/kg
Talc (non asbestiform)	oral	LD50 Rat: >5000 mg/kg
Titanium Dioxide	oral	LD50 Mouse: > 5000 mg/kg
	inhalation	LC50 Rat: 5.09 mg/L (4 hr)

Skin corrosion/irritation

Assessment:

Causes skin irritation.

Product data:

No data available.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 7 of 12

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part A

Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Causes skin irritation.
P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Causes skin irritation.

Serious eye damage/irritation

Assessment:

Causes serious eye irritation.

Product data:

No data available.

Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Causes serious eye irritation.
P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Causes serious eye irritation.

Respiratory or skin sensitization

Assessment:

May cause an allergic skin reaction.

Product data:

No data available.

Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	May cause an allergic skin reaction.
P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Species	Result
Talc (non asbestiform)		Talc containing asbestos is carcinogenic to humans.
Glass, oxide, chemicals	Not applicable	May cause cancer via inhalation.
Titanium Dioxide	Not applicable.	Airborne, unbound particles of respirable size are known to cause cancer.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 8 of 12

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part A

International Agency for Research on Cancer (IARC):

Name	Classification
Talc (non asbestiform)	Group 3
Glass, oxide, chemicals	Group 2B
Titanium Dioxide	Group 2B

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

Skin, Eye.

Symptoms related to the physical, chemical and toxicological characteristics:

Refer to Section 4 of this SDS.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 9 of 12

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part A

Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	EC50 Scenedesmus capricornutum: 9 mg/L (48 hr)
	EC50 Daphnia magna: 1 mg/L (48 hr)

Chronic (long-term) toxicity

Assessment:

Toxic to aquatic life with long lasting effects.

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	No biodegradation observed. However, significant hydrolysis occurred eliminating 82 % over 28 days.
P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Under test conditions, no biodegradation was observed (11% degradation after 28 days).
Talc (non asbestiform)	Biodegradation is not applicable to inorganic substances.
Titanium Dioxide	Degradation/biodegradation testing is not relevant for metals and metal compounds that are not (bio)degradable, including titanium dioxide.

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Talc (non asbestiform)	No potential for bioaccumulation.

Mobility in soil

Product data: No data available.

Substance data:

Name	Result
P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Moderately mobile (log Koc: 2.88).

Results of PBT and vPvB assessment

Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 10 of 12

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part A

Substance data:

PBT assessment:

P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	This substance is not PBT.
Talc (non asbestiform)	The substance is inorganic, and as such the criteria for PBT are not applicable.
Titanium Dioxide	According to Annex XIII of regulation (EC) 1907/2006 a PBT assessment shall not be conducted for inorganic substances. Titanium dioxide is an inorganic substance, thus a PBT assessment is not required.

vPvB assessment:

P-tert-butylphenyl 1-(2,3-epoxy)propyl ether	This substance is not vPvB.
Talc (non asbestiform)	The substance is inorganic, and as such the criteria for vPvB are not applicable.
Titanium Dioxide	According to Annex XIII of regulation (EC) 1907/2006 a vPvB assessment shall not be conducted for inorganic substances. Titanium dioxide is an inorganic substance, thus a vPvB assessment is not required.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport information

Australian Dangerous Goods (ADG)

UN number	UN3077
UN proper shipping name	Environmentally hazardous substance, solid, N.O.S. (Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran and P-tert-butylphenyl 1-(2,3-epoxy)propyl ether)
UN transport hazard class(es)	9 
Packing group	III
Environmental hazards	Marine Pollutant (Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran and P-tert-butylphenyl 1-(2,3-epoxy)propyl ether)
Special precautions for user	None
Hazchem/Emergency Action Code	2Z
Additional Information	This product is being shipped as a limited quantity, packaged in quantities below 5 kg, in accordance with the ADG Code.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations


Initial preparation date: 01.19.2017

Page 11 of 12


Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part A

International Maritime Dangerous Goods (IMDG)

UN number	UN3077
UN proper shipping name	Environmentally hazardous substance, solid, N.O.S. (Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran and P-tert-butylphenyl 1-(2,3-epoxy)propyl ether)
UN transport hazard class(es)	9 
Packing group	III
Environmental hazards	Marine Pollutant (Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran and P-tert-butylphenyl 1-(2,3-epoxy)propyl ether)
Special precautions for user	None
EMS number	F-A, S-F
Stowage category	Category A
Excepted quantities	E1
Limited quantity	5 kg
Additional Information	This product is being shipped as a limited quantity, packaged in quantities below 5 kg, in accordance with the IMDG Code.

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	UN3077
UN proper shipping name	Environmentally hazardous substance, solid, N.O.S. (Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran and P-tert-butylphenyl 1-(2,3-epoxy)propyl ether)
UN transport hazard class(es)	9 
Packing group	III
Environmental hazards	Marine Pollutant (Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran and P-tert-butylphenyl 1-(2,3-epoxy)propyl ether)
Special precautions for user	None
ERG code	9L
Excepted quantities	E1
Passenger and cargo	400 kg
Cargo aircraft only	400 kg
Limited quantity	30 kg G
Additional Information	This product is being shipped as a limited quantity, packaged in quantities below 30 kg G, in accordance with the IATA Dangerous Goods Regulations.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 12 of 12

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part A

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Bulk Name	None
Ship type	None
Pollution category	None

SECTION 15: Regulatory information

Australia regulations

Australian Inventory of Chemical Substances (AICS): All ingredients are listed or exempt.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP): None of the ingredients are listed.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This SDS was authored in accordance with the Australian Work Health and Safety Regulations and supplemented by the Australian Code of Practice on the Preparation of Safety Data Sheets for Hazardous Chemicals. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 01.19.2017

Revision date: 07.09.2020

Revision Notes:

Revision Date	Notes
2020-07-09	Classification and composition change.

Additional information:

Version 2

End of Safety Data Sheet

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 1 of 11

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part B

SECTION 1: Identification

Product identifier

Product name: Epoxy Putty Stick - Steel - Part B

Product code: 8267AUS



Recommended use of the product and restriction on use

Relevant identified uses: Not determined or not applicable.

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

J-B Weld Company, LLC
400 CMH Road
Sulphur Springs, TX 75482
903-885-7696

Supplier:

Australia

HPP Lunds
1/195 Jackson Rd
Sunnybank Hills, Qld 4109
1300-306-781

Emergency telephone number:

Australia

InfoTrac

1300-366-961 (24 hours)

SECTION 2: Hazard(s) identification

GHS classification:

Skin sensitization, category 1

Label elements

Hazard pictograms:



Signal word: Warning

Hazard statements:

H317 May cause an allergic skin reaction

Precautionary statements:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray

P272 Contaminated work clothing should not be allowed out of the workplace

P280 Wear face protection

P321 Specific treatment (see supplemental first aid instruction on this label)

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P363 Wash contaminated clothing before reuse

P501 Dispose of contents/container in accordance with local regulations.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 2 of 11

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part B

Hazards not otherwise classified:

None

SECTION 3: Composition and information on ingredients

Identification	Name	Weight %
CAS number: 72244-98-5	Poly(oxy(methyl-1,2-ethanediyl)), alpha-hydro-omega-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	10-30
CAS number: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	<5
CAS number: 65997-17-3	Glass, oxide, chemicals	10-30
CAS number: 14807-96-6	Talc (non asbestiform)	30-60
CAS number: 1333-86-4	Bounded Carbon Black	<1

Additional Information:

CAS # 65997-17-3 is classified as a carcinogen in its inhalable form. Since the fiberglass powder in this product is not inhalable, the product itself is not classified as a carcinogen in the form presented.

Carbon black is classified as a carcinogen only in its respirable form. Since the carbon black in this product is not respirable, the product itself is not classified as a carcinogen in the form presented.

SECTION 4: First aid measures

Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance.

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 3 of 11

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part B

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Treat symptomatically.

SECTION 5: Fire fighting measures

Extinguishing media

Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable extinguishing media:

Do not use water jet.

Specific hazards during fire-fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 4 of 11

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part B

SECTION 7: Handling and storage precautions

Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure controls and personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Australia	Glass, oxide, chemicals	65997-17-3	TWA: 0.5 fibers/ml (of air [Superfine glass fiber])
	Glass, oxide, chemicals	65997-17-3	TWA: 0.5 fibers/ml (of air [Synthetic mineral fibers])
	Glass, oxide, chemicals	65997-17-3	TWA: 0.5 fibers/ml (of air [Glasswool including superfine glass fiber])
	Glass, oxide, chemicals	65997-17-3	TWA: 0.5 fibers/ml (of air [Rockwool])
	Glass, oxide, chemicals	65997-17-3	TWA: 0.5 fibers/ml (of air [Ceramic fibers])
	Talc (non asbestiform)	14807-96-6	TWA: 2.5 mg/m ³ (containing no asbestos fibers)
	Bounded Carbon Black	1333-86-4	8-Hour TWA: 3 mg/m ³ (Workplace Exposure Standards for Airborne Contaminants)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Not determined or not applicable.

Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal protection equipment

Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 5 of 11

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part B

recognized national standards (or equivalent).

Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Very thick grey paste (solid)
Odor	Not determined or not available.
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	148.89 °C (300 °F)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	2.1 g/cm ³
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 6 of 11

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part B

SECTION 10: Stability and reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible materials:

None known.

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Hazard information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
2,4,6-tris(dimethylaminomethyl)phenol	oral	LD50 Rat: 1200 mg/kg
Talc (non asbestiform)	oral	LD50 Rat: >5000 mg/kg
Bounded Carbon Black	oral	LD50 Rat: >15400 mg/kg
	dermal	LD50 Rabbit: >3000 mg/kg

Skin corrosion/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
2,4,6-tris(dimethylaminomethyl)phenol	Causes skin irritation.

Serious eye damage/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
2,4,6-tris(dimethylaminomethyl)phenol	Causes serious eye irritation.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 7 of 11

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part B

Respiratory or skin sensitization

Assessment:

May cause an allergic skin reaction.

Product data:

No data available.

Substance data:

Name	Result
Poly(oxy(methyl-1,2-ethanediyl)), alpha-hydro-omega-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Species	Result
Glass, oxide, chemicals	Not applicable	May cause cancer via inhalation.
Talc (non asbestiform)		Talc containing asbestos is carcinogenic to humans.
Bounded Carbon Black	Not applicable.	The carcinogenic classification only applies to airborne, unbound particles of respirable size.

International Agency for Research on Cancer (IARC):

Name	Classification
Glass, oxide, chemicals	Group 2B
Talc (non asbestiform)	Group 3
Bounded Carbon Black	Group 2B

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 8 of 11

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part B

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

Skin exposure.

Symptoms related to the physical, chemical and toxicological characteristics:

Refer to Section 4 of this SDS.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Chronic (long-term) toxicity

Assessment:

Harmful to aquatic life with long lasting effects.

Product data: No data available.

Substance data:

Name	Result
Poly(oxy(methyl-1,2-ethanediyl)), alpha-hydro-omega-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	NOEC Daphnia magna (Water flea): 3.5 mg/L (21 d)

Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
2,4,6-tris(dimethylaminomethyl)phenol	Not readily biodegradable in water (4% degradation after 28 days).
Talc (non asbestiform)	Biodegradation is not applicable to inorganic substances.
Bounded Carbon Black	The substance will not be biodegraded.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 9 of 11

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part B

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Talc (non asbestiform)	No potential for bioaccumulation.
Bounded Carbon Black	Bioaccumulation is not expected to occur.

Mobility in soil

Product data: No data available.

Substance data:

Name	Result
2,4,6-tris(dimethylaminomethyl)phenol	Mobile (Koc: 20.98 L/kg).

Results of PBT and vPvB assessment

Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance data:

PBT assessment:

2,4,6-tris(dimethylaminomethyl)phenol	This substance is not PBT.
Talc (non asbestiform)	The substance is inorganic, and as such the criteria for PBT are not applicable.
Bounded Carbon Black	The substance is not PBT.

vPvB assessment:

2,4,6-tris(dimethylaminomethyl)phenol	This substance is not vPvB.
Talc (non asbestiform)	The substance is inorganic, and as such the criteria for vPvB are not applicable.
Bounded Carbon Black	The substance is not vPvB.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

Contaminated packages:

Not determined or not applicable.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 10 of 11

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part B

SECTION 14: Transport information

Australian Dangerous Goods (ADG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Bulk Name	None
Ship type	None
Pollution category	None

SECTION 15: Regulatory information

Australia regulations

Australian Inventory of Chemical Substances (AICS): All ingredients are listed or exempt.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP): None of the ingredients are listed.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 01.19.2017

Page 11 of 11

Revision date: 07.09.2020

Epoxy Putty Stick - Steel - Part B

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This SDS was authored in accordance with the Australian Work Health and Safety Regulations and supplemented by the Australian Code of Practice on the Preparation of Safety Data Sheets for Hazardous Chemicals. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 01.19.2017

Revision date: 07.09.2020

Revision Notes:

Revision Date	Notes
2020-07-09	Classification and composition change.

Additional information:

Version 2

End of Safety Data Sheet