

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 30/07/2020 Revision date: 08/02/2023 Version: 6.1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier Product form : Mixture : TUFGEAR Spray Trade name Vaporizer : Aerosol 1.2. Relevant identified uses of the substance or mixture and uses advised against 1.2.1. Relevant identified uses Main use category : Industrial use, Professional use Industrial/Professional use spec : For professional use only Industrial Use of the substance/mixture : Lubricants, Greases and Release Products 1.2.2. Uses advised against Restrictions on use : Acetone is listed as a reportable explosives precursor in Annex II of EU regulation 2019/1148

#### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

ROCOL a division of ITW Ltd Rocol House Wakefield Rd, Swillington LS26 8BS Leeds – West Yorkshire United Kingdom T +44 (0)113 232 2600 customer.service@rocol.com - www.rocol.com

#### 1.4. Emergency telephone number

#### Emergency number

: +44 (0)113 232 2600

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals

H222;H229

H315

H336

H412

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 Skin corrosion/irritation, Category 2 Specific target organ toxicity – Single exposure, Category 3, Narcosis Hazardous to the aquatic environment – Chronic Hazard, Category 3 Full text of H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]		
Hazard pictograms (CLP)		
	GHS02 GHS07	
Signal word (CLP)	: Danger	
Contains	: HYDROCARBONS C7-C9, ISOALKANES; ACETONE	
Hazard statements (CLP)	: H222 - Extremely flammable aerosol.	
	H229 - Pressurised container: May burst if heated.	
	H315 - Causes skin irritation.	
	H336 - May cause drowsiness or dizziness.	
	H412 - Harmful to aquatic life with long lasting effects.	
Precautionary statements (CLP)	<ul> <li>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P211 - Do not spray on an open flame or other ignition source.</li> <li>P251 - Do not pierce or burn, even after use.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> </ul>	
	P280 - Wear protective gloves, protective clothing, eye protection, face protection.	
	P302+P352 - IF ON SKIN: Wash with plenty of water.	
	P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
0.0 Other herende		

#### 2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component		
HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE)(68476-85-7)	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %	

## **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

#### Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) substance with national workplace exposure limit(s) (GB) (Note K)(Note S)(Note U)	CAS-No.: 68476-85-7 EC-No.: 270-704-2 EC Index-No.: 649-202-00-6 REACH-no: Exempt	50 – 70	Flam. Gas 1A, H220 Press. Gas (Comp.), H280 Flam. Liq. Not classified Muta. Not classified Carc. Not classified
HYDROCARBONS C7-C9, ISOALKANES	CAS-No.: 64741-66-8 EC-No.: 921-728-3 REACH-no: 01-2119471305- 42	15 – 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
TALC substance with national workplace exposure limit(s) (GB)	CAS-No.: 14807-96-6 EC-No.: 238-877-9 REACH-no: Exempt	2.4 – 5	Not classified
ACETONE substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330- 49	2.4 – 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
CALCIUM CARBONATE substance with national workplace exposure limit(s) (GB)	CAS-No.: 1317-65-3 EC-No.: 2151-79-6 REACH-no: Exempt - Annex V	1 – 2.4	Not classified

Note K: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply.

Note S: This substance may not require a label according to Article 17 (see Section 1.3 of Annex I) (Table 3).

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:. Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case. Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures				
4.1. Description of first aid measures				
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).			
First-aid measures after inhalation	<ul> <li>Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.</li> </ul>			
First-aid measures after skin contact	: Wash with plenty of water/ If skin irritation occurs: Get medical advice/attention.			
First-aid measures after eye contact	: Direct contact with the eyes is likely to be irritating. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.			
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.			
4.2. Most important symptoms and effects, both acute and delayed				
Symptoms/effects after inhalation Symptoms/effects after skin contact	<ul><li>Shortness of breath. May cause drowsiness or dizziness.</li><li>Causes skin irritation.</li></ul>			

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	<ul><li>Foam. Dry powder. Carbon dioxide. Water spray. Sand.</li><li>Do not use a heavy water stream.</li></ul>

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.2. Special hazards arising from the substance or mixture		
Fire hazard Explosion hazard	<ul> <li>Extremely flammable aerosol.</li> <li>Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.</li> </ul>	
5.3. Advice for firefighters		
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. DO NOT fight fire when fire reaches explosives. Evacuate area.	
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.	

SECTION 6: Accidental release measures		
6.1. Personal precautions, prote	ctive equipment and emergency procedures	
General measures	: No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.	
6.1.1. For non-emergency personnel		
Emergency procedures	: Evacuate unnecessary personnel.	
6.1.2. For emergency responders		
Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapours/spray.	
Emergency procedures	: Ventilate area.	
6.2. Environmental precautions		

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up	
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

## 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage	e
7.1. Precautions for safe handling	
Additional hazards when processed Precautions for safe handling Hygiene measures	<ul> <li>Hazardous waste due to potential risk of explosion. Do not pierce or burn, even after use.</li> <li>Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Do not spray on an open flame or other ignition source. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.</li> <li>Wash hands, forearms and face thoroughly after handling.</li> </ul>
7.2. Conditions for safe storage, inclu	uding any incompatibilities
Technical measures Storage conditions Incompatible products Incompatible materials	<ul> <li>Proper grounding procedures to avoid static electricity should be followed.</li> <li>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.</li> <li>Strong bases. Strong acids.</li> <li>Sources of ignition. Direct sunlight. Heat sources.</li> </ul>
7.3. Specific end use(s)	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 3: Exposure controls/personal protection         8.1. Control parameters         8.1.1 Netional occupational exposure and biological limit values         CALCIUM CARBONATE (1317-65-3)         United Kingdom - Occupational Exposure Limits         Local name       Calcium carbonate (Limestone, Marbie)         WEL TWA (CEL TWA) [1]       10 mg/m² tela inhalable         4 ng/m² tela inhalable       4 ng/m² tela inhalable         Account (14807-86-6)       United Kingdom - Occupational Exposure Limits         Local name       Talc         Regulatory reference       EH40/2005 (Fourth editor, 2020), HSE         Account aname       Talc         Regulatory ference       EH40/2005 (Fourth editor, 2020), HSE         ACETONE (67-64-1)       EU - Indicative Occupational Exposure Limits (IOEL)         Local name       Acetone         OBL TWA (DEL TWA) [1]       500 ppm         Regulatory reference       COMMISSION DIRECTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limits       200 ppm         Local name       Acetone         Vel. TWA (DEL TWA) [1]       500 ppm         Regulatory reference       EVOMISSION DIRECTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limits       200 og/m²         Local name       Acetone <tr< th=""><th colspan="3"></th></tr<>				
A.1. National occupational exposure and biological limit values         CALCIUM CARBONATE (1317-65-3)         United Kingdom - Occupational Exposure Limits         Local name       Calcium carbonate (Limestone, Marbie)         WEL TWA (OEL TWA) [1]       10 mg/m² total inhalable 4 mg/m² respinable         Regulatory reference       EH40/2005 (Fourth edition, 2020). HSE         TALC (14807-96-6)       Talc         United Kingdom - Occupational Exposure Limits       Talc         Regulatory reference       Talc         Regulatory reference       EH40/2006 (Fourth edition, 2020). HSE         Regulatory reference       Talc         Regulatory reference       EH40/2006 (Fourth edition, 2020). HSE         ACETONE (67-64-1)       10 mg/m² respinable dust         EU - Indicativo Occupational Exposure Limit (IOEL)       Local name         ACETONE (67-64-1)       210 mg/m²         EU - Indicativo Occupational Exposure Limit (IOEL)       Local name         Acetone       CoMINISSION DIRECTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limit (IOEL)       Local name         Vel TWA (OEL TWA) [1]       1210 mg/m²         USU TWA (OEL TWA) [2]       500 pm         WEL TWA (OEL TWA) [1]       1210 mg/m²         WEL TWA (OEL TWA) [2]       500 pm         W	SECTION 8: Exposure controls/personal protection			
CALCIUM CARBONATE (1317-65-3)           United Kingdom - Occupational Exposure Limits           Local name         Calcium carbonate (Linestone, Marble)           WEL TWA (OEL TWA) [1]         10 mg/m² total inhalable 4 mg/m² respirable           Regulatory reference         EH40/2005 (Fourth edition, 2020). HSE           TALC (14807-96-6)         United Kingdom - Occupational Exposure Limits           Local name         Tale           WEL TWA (OEL TWA) [1]         1 mg/m² respirable dust           Regulatory reference         EH40/2005 (Fourth edition, 2020). HSE           ACETONE (67-64-1)         EU           EU - Indicative Occupational Exposure Limit (IOEL)         Local name           Local name         Acetone           IOEL TWA         1210 mg/m²           IOEL TWA         1210 mg/m²           IOEL TWA         1210 mg/m²           Local name         Acetone           Outied Kingdom - Occupational Exposure Limits         Local name           Local name         Acetone           United Kingdom - Occupational Exposure Limits         Local name           Local name         Acetone           United Kingdom - Occupational Exposure Limits         Local name           Local name         Acetone           WEL TWA (OEL TWA) [2]         360 ppm<	8.1. Control parameters			
United Kingdom - Occupational Exposure Limits           Local name         Calcium carbonate (Limestone, Marble)           WEL TWA (OEL TWA) [1]         10 mg/m² total inhalable 4 mg/m² respirable           Regulatory reference         EH40/2005 (Fourth edition, 2020), HSE           TALC (14807-96-6)         United Kingdom - Occupational Exposure Limits           Local name         Talc           WEL TWA (OEL TWA) [1]         1 mg/m² respirable dust           Regulatory reference         EH40/2005 (Fourth edition, 2020), HSE           ACETONE (67-64-1)         EU           EU - Indicative Occupational Exposure Limit (0EU-           Local name         Acetone           IOEL TWA         1210 mg/m²           IOEL TWA         500 ppm           Regulatory reference         COMMISSION DIRECTIVE 2000/39/EC           United Kingdom - Occupational Exposure Limits         Cacioname           IOEL TWA         1210 mg/m²           United Kingdom - Occupational Exposure Limits         Cacioname           United Kingdom - Occupational Exposure Limits         CodMMISSION DIRECTIVE 2000/39/EC           United Kingdom - Occupational Exposure Limits         So0 ppm           Regulatory reference         Acetone           WEL TWA (OEL TWA) [2]         500 ppm           WEL TWA (OEL TWA) [2]	8.1.1 National occupational exposure and biological limit values			
Local name         Calcium carbonate (Limestone, Marble)           WEL TWA (OEL TWA) [1]         10 mg/m² total inhalable 4 mg/m² respirable           Regulatory reference         Et40/2005 (Fourth edition, 2020), HSE           TALC (14807-96-6)         United Kingdom - Occupational Exposure Limits           Local name         Talc           WEL TWA (OEL TWA) [1]         1 mg/m² respirable dust           Regulatory reference         EH40/2005 (Fourth edition, 2020), HSE           ACETONE (67-64-1)         EU - Indicative Occupational Exposure Limit (IOEL)           Local name         Acetone           IOEL TWA         1210 mg/m²           Local name         Acetone           OEL TWA         1210 mg/m²           Local name         Acetone           United Kingdom - Occupational Exposure Limits         Eucename           Local name         Acetone           United Kingdom - Occupational Exposure Limits         Eucename           Local name         Acetone           WEL TWA (OEL TWA) [1]         1210 mg/m²           WEL TWA (OEL TWA) [2]         500 ppm           WEL STEL (OEL STEL)         3620 mg/m²           WEL STEL (OEL STEL)         3600 ppm           WEL STEL (OEL STEL)         1500 ppm           Regulatory reference	CALCIUM CARBONATE (1317-65-3)			
WEL TWA (OEL TWA) [1]         10 mg/m² total inhalable 4 mg/m² respirable           Regulatory reference         EH40/2005 (Fourth edition, 2020). HSE           TALC (14807-86-6)         Taic           United Kingdom - Occupational Exposure Limits         I mg/m² respirable dust           Regulatory reference         Taic           WEL TWA (OEL TWA) [1]         1 mg/m² respirable dust           Regulatory reference         EH40/2005 (Fourth edition, 2020). HSE           ACETONE (67-64-1)         EU - Indicative Occupational Exposure Limit (IOEL)           Local name         Acetone           IOEL TWA (DEL TWA) [1]         500 ppm           Regulatory reference         COMMISSION DIRECTIVE 2000/39/EC           United Kingdom - Occupational Exposure Limits         Edote           United Kingdom - Occupational Exposure Limits         S00 ppm	United Kingdom - Occupational Exposure Limits			
Amg/m <sup>2</sup> respirable           Regulatory reference         EH40/2005 (Fourth edition, 2020). HSE           TALC (14807-96-6)           United Kingdom - Occupational Exposure Limit/           Local name         Talc           WEL TWA (OEL TWA) [1]         Img/m <sup>2</sup> respirable dust           Regulatory reference         EH40/2005 (Fourth edition, 2020). HSE           ACETORE (67-64-1)           EU-Indicative Occupational Exposure Limit (IOEL           Local name           Acetone           IOEL TWA (0EL TWA) [1]           Acetone           IOEL INDICE (57-64-1)           EU-Indicative Occupational Exposure Limit (IOEL           Local name           Acetone           IOEL TWA (ppm]           Regulatory reference           OCMMISSION DIRECTIVE 2000/39/EC           United Kingdom - Occupational Exposure Limit (IOEL           Local name           Acetone           OLITIES (DEL TWA) [2]           OCMINSSION DIRECTIVE 2000/39/EC           UNITED TWA (OEL TWA) [2]           SoD ppm           Regulatory r	Local name	Calcium carbonate (Limestone, Marble)		
TALC (14807-86-6)         United Kingdom - Occupational Exposure Limits         Local name       Talc         WEL TWA (OEL TWA) [1]       1 mg/m³ respirable dust         Regulatory reference       EH40/2005 (Fourth edition, 2020). HSE         ACETONE (67-64-1)       EU         EU - Indicative Occupational Exposure Limit (IOEL)       Local name         Local name       Acetone         IOEL TWA       1210 mg/m³         IOEL TWA (ppm]       500 ppm         Regulatory reference       COMMISSION DIRECTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limits       Codmission DirecTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limits       Codmission DirecTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limits       Codmission DirecTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limits       Codmission DirecTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limits       Local name         WeL TWA (OEL TWA) [1]       1210 mg/m³         WEL STEL (OEL STEL)       3620 mg/m³         WEL STEL (OEL STEL) [ppm]       1500 ppm         Regulatory reference       EH40/2005 (Fourth edition, 2020). HSE         HYDROCARBON AEROSOL PROPELLANT (<-J*% 1,3-BUTADIENE) (68476-85-7)	WEL TWA (OEL TWA) [1]			
United Kingdom - Occupational Exposure Limits           Local name         Talc           WEL TWA (OEL TWA) [1]         1 mg/m³ respirable dust           Regulatory reference         EH40/2005 (Fourth edition, 2020). HSE           ACETONE (67-64-1)         EU - Indicative Occupational Exposure Limit (IOEL)           Eucal name         Acetone           IOEL TWA         1210 mg/m³           IOEL TWA         500 ppm           Regulatory reference         COMMISSION DIRECTIVE 2000/39/EC           United Kingdom - Occupational Exposure Limits         Codenne           Uccal name         Acetone           VEL TWA (OEL TWA) [1]         1210 mg/m³           United Kingdom - Occupational Exposure Limits         United Kingdom - Occupational Exposure Limits           Local name         Acetone           WEL TWA (OEL TWA) [1]         1210 mg/m³           WEL TWA (OEL TWA) [2]         500 ppm           WEL STEL (OEL STEL)         3620 mg/m³           WEL STEL (OEL STEL) [ppm]         1500 ppm           Regulatory reference         EH40/2005 (Fourth edition, 2020). HSE           HYDROCARBON AEROSOL PROPELLANT ( <j: (68476-85-7)<="" a:butadiene)="" j:="" td="">         United Kingdom - Occupational Exposure Limits           Local name         Liquefied petroleum gas           WEL TWA (OEL TWA) [1]</j:>	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
Local name       Talc         WEL TWA (OEL TWA) [1]       1 mg/m³ respirable dust         Regulatory reference       EH40/2005 (Fourth edition, 2020). HSE         ACETONE (67-64-1)       EU - Indicative Occupational Exposure Limit (IOEL)         Local name       Acetone         IOEL TWA       1210 mg/m³         IOEL TWA       1210 mg/m³         IOEL TWA       500 ppm         Regulatory reference       COMMISSION DIRECTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limits       Colone         Local name       Acetone         WEL TWA (OEL TWA) [1]       1210 mg/m³         WEL TWA (OEL TWA) [2]       500 ppm         WEL TWA (OEL TWA) [2]       500 ppm         WEL STEL (OEL STEL)       3620 mg/m³         WEL STEL (OEL STEL) [ppm]       1500 ppm         Regulatory reference       EH40/2005 (Fourth edition, 2020). HSE         HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) (68476-85-7)	TALC (14807-96-6)			
WEL TWA (OEL TWA) [1]       1 mg/m³ respirable dust         Regulatory reference       EH40/2005 (Fourth edition, 2020). HSE         ACETONE (67-64-1)       EU - Indicative Occupational Exposure Limit (IOEL)         Local name       Acetone         IOEL TWA       1210 mg/m³         IOEL TWA       500 ppm         Regulatory reference       COMINISSION DIRECTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limits       Local name         Vectorul (QEL TWA) [1]       1210 mg/m³         Wel TWA (OEL TWA) [2]       500 ppm         Wel TWA (OEL TWA) [2]       500 ppm         WEL TWA (OEL TWA) [2]       500 ppm         WEL STEL (OEL STEL)       3620 mg/m³         WEL STEL (OEL STEL) [ppm]       1500 ppm         Regulatory reference       EH40/2005 (Fourth editon, 2020). HSE         HYDROCARBON AEROSOL PROPELLANT (       1,3-BUTADIENE) (68476-85-7)         United Kingdom - Occupational Exposure Limits       Local name         Local name       Liquefied petroleum gas         WEL TWA (OEL TWA) [1]       1750 mg/m³         WEL TWA (OEL TWA) [2]       1000 ppm	United Kingdom - Occupational Exposure Limits			
Regulatory reference       EH40/2005 (Fourth edition, 2020). HSE         ACETONE (67-64-1)       EU - Indicative Occupational Exposure Limit (IOEL)         Local name       Acetone         IOEL TWA       1210 mg/m³         IOEL TWA (ppm]       500 ppm         Regulatory reference       COMMISSION DIRECTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limits       COMMISSION DIRECTIVE 2000/39/EC         Local name       Acetone         WEL TWA (OEL TWA) [1]       1210 mg/m³         WEL TWA (OEL TWA) [2]       500 ppm         WEL TWA (OEL TWA) [2]       500 ppm         WEL STEL (OEL STEL)       3620 mg/m³         WEL STEL (OEL STEL)       3620 mg/m³         WEL STEL (OEL STEL) (ppm]       1500 ppm         Regulatory reference       EH40/2005 (Fourth edition, 2020). HSE         HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) (68476-85-7)	Local name	Talc		
ACETONE (67-64-1)         EU - Indicative Occupational Exposure Limit (IOEL)         Local name       Acetone         IOEL TWA       1210 mg/m³         IOEL TWA [ppm]       500 ppm         Regulatory reference       COMMISSION DIRECTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limits       Codmission Directive 2000/39/EC         United Kingdom - Occupational Exposure Limits       Local name         VEL TWA (OEL TWA) [1]       1210 mg/m³         WEL TWA (OEL TWA) [2]       500 ppm         WEL STEL (OEL STEL)       3620 mg/m³         WEL STEL (OEL STEL)       3620 mg/m³         WEL STEL (OEL STEL) [ppm]       1500 ppm         Regulatory reference       EH40/2005 (Fourth edition, 2020). HSE         HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) (68476-85-7)	WEL TWA (OEL TWA) [1]	1 mg/m³ respirable dust		
EU - Indicative Occupational Exposure Limit (IOEL)         Local name       Acetone         IOEL TWA       1210 mg/m³         IOEL TWA (ppm)       500 ppm         Regulatory reference       COMMISSION DIRECTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limits       Codmission Directive 2000/39/EC         United Kingdom - Occupational Exposure Limits       Codmission Directive 2000/39/EC         United Kingdom - Occupational Exposure Limits       Local name         WEL TWA (OEL TWA) [1]       1210 mg/m³         WEL TWA (OEL TWA) [2]       500 ppm         WEL STEL (OEL STEL)       3620 mg/m³         WEL STEL (OEL STEL) [ppm]       1500 ppm         Regulatory reference       EH40/2005 (Fourth edition, 2020). HSE         HYDROCARBON AEROSOL PROPELLANT (       1,3-BUTADIENE) (68476-85-7)         United Kingdom - Occupational Exposure Limits       Liquefied petroleum gas         United Kingdom - Occupational Exposure Limits       Local name         Uccal name       Liquefied petroleum gas         WEL TWA (OEL TWA) [2]       1000 ppm         WEL TWA (OEL TWA) [2]       1000 ppm         WEL STEL (OEL STEL)       2180 mg/m³         WEL TWA (OEL TWA) [2]       1000 ppm         WEL STEL (OEL STEL) [ppm]       1250 ppm         WEL	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
Local nameAcetoneIOEL TWA1210 mg/m³IOEL TWA [ppm]500 ppmRegulatory referenceCOMMISSION DIRECTIVE 2000/39/ECUnited Kingdom - Occupational Exposure LimitsLocal nameAcetoneWEL TWA (OEL TWA) [1]1210 mg/m³WEL TWA (OEL TWA) [2]500 ppmWEL STEL (OEL STEL)3620 mg/m³WEL STEL (OEL STEL)3620 mg/m³WEL STEL (OEL STEL) [ppm]1500 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEHYDROCARBON AEROSOL PROPELLANT (1% 1,3-BUTADIENE) (68476-85-7)United Kingdom - Occupational Exposure LimitsLocal nameLiquefied petroleum gasWEL TWA (OEL TWA) [1]1750 mg/m³WEL TWA (OEL TWA) [2]1000 ppmWEL TWA (OEL TWA) [2]1000 ppmWEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL)1250 ppmRemarkCarc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))	ACETONE (67-64-1)			
IOEL TWA1210 mg/m³IOEL TWA [ppm]500 pmRegulatory referenceCOMMISSION DIRECTIVE 2000/39/ECUnited Kingdom - Occupational Exposure LimitsLocal nameAcetoneWEL TWA (OEL TWA) [1]1210 mg/m³WEL TWA (OEL TWA) [2]500 ppmWEL STEL (OEL STEL)3620 mg/m³WEL STEL (OEL STEL) [ppm]1500 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEHYDROCARBON AEROSOL PROPELLANT ( <u% (68476-85-7)<="" 1,3-butadiene)="" td="">United Kingdom - Occupational Exposure LimitsLocal nameLiquefied petroleum gasWEL TWA (OEL TWA) [2]1000 ppmWEL STEL (OEL STEL)1750 mg/m³WEL STEL (OEL TWA) [2]1000 ppmWEL TWA (OEL TWA) [2]1000 ppmWEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL) [ppm]1250 ppmRemarkCarc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))</u%>	EU - Indicative Occupational Exposure Limit (IOEL)			
IOEL TWA [ppm]500 ppmRegulatory referenceCOMMISSION DIRECTIVE 2000/39/ECUnited Kingdom - Occupational Exposure LimitsLocal nameAcetoneWEL TWA (OEL TWA) [1]1210 mg/m³WEL TWA (OEL TWA) [2]500 ppmWEL STEL (OEL STEL)3620 mg/m³WEL STEL (OEL STEL) [ppm]1500 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEHYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) (68476-85-7)	Local name	Acetone		
Regulatory reference       COMMISSION DIRECTIVE 2000/39/EC         United Kingdom - Occupational Exposure Limits       Acetone         Local name       Acetone         WEL TWA (OEL TWA) [1]       1210 mg/m³         WEL TWA (OEL TWA) [2]       500 ppm         WEL STEL (OEL STEL)       3620 mg/m³         WEL STEL (OEL STEL) [ppm]       1500 ppm         Regulatory reference       EH40/2005 (Fourth edition, 2020). HSE         HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) (68476-85-7)	IOEL TWA	1210 mg/m <sup>3</sup>		
United Kingdom - Occupational Exposure Limits         Local name       Acetone         WEL TWA (OEL TWA) [1]       1210 mg/m³         WEL TWA (OEL TWA) [2]       500 ppm         WEL STEL (OEL STEL)       3620 mg/m³         WEL STEL (OEL STEL) [ppm]       1500 ppm         Regulatory reference       EH40/2005 (Fourth edition, 2020). HSE         HYDROCARBON AEROSOL PROPELLANT (       1,3-BUTADIENE) (68476-85-7)         United Kingdom - Occupational Exposure Limits       Local name         Local name       Liquefied petroleum gas         WEL TWA (OEL TWA) [1]       1750 mg/m³         WEL TWA (OEL TWA) [2]       1000 ppm         WEL STEL (OEL STEL)       2180 mg/m³         WEL STEL (OEL STEL)       2180 mg/m³         WEL STEL (OEL STEL) [ppm]       1250 ppm         Remark       Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1.3-diene))	IOEL TWA [ppm]	500 ppm		
Local nameAcetoneWEL TWA (OEL TWA) [1]1210 mg/m³WEL TWA (OEL TWA) [2]500 ppmWEL STEL (OEL STEL)3620 mg/m³WEL STEL (OEL STEL) [ppm]1500 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEHYDROCARBON AEROSOL PROPELLANT (1% 1,3-BUTADIENE) (68476-85-7)United Kingdom - Occupational Exposure LimitsLocal nameLiquefied petroleum gasWEL TWA (OEL TWA) [1]1750 mg/m³WEL TWA (OEL TWA) [2]1000 ppmWEL STEL (OEL STEL)2180 mg/m³WEL	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
WEL TWA (OEL TWA) [1]1210 mg/m³WEL TWA (OEL TWA) [2]500 ppmWEL STEL (OEL STEL)3620 mg/m³WEL STEL (OEL STEL) [ppm]1500 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEHYDROCARBON AEROSOL PROPELLANT (1/3-BUTADIENE) (68476-85-7)United Kingdom - Occupational Exposure LimitsLiquefied petroleum gasLocal nameLiquefied petroleum gasWEL TWA (OEL TWA) [1]1750 mg/m³WEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL) [ppm]1250 ppmRemarkCarc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))	United Kingdom - Occupational Exposure Limits			
WEL TWA (OEL TWA) [2]500 ppmWEL STEL (OEL STEL)3620 mg/m³WEL STEL (OEL STEL) [ppm]1500 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEHYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) (68476-85-7)	Local name	Acetone		
WEL STEL (OEL STEL)3620 mg/m³WEL STEL (OEL STEL) [ppm]1500 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEHYDROCARBON AEROSOL PROPELLANT ( <utv (68476-85-7)<="" 1,3-butadiene)="" td="">United Kingdom - Occupational Exposure LimitsLocal nameLiquefied petroleum gasWEL TWA (OEL TWA) [1]1750 mg/m³WEL TWA (OEL TWA) [2]1000 ppmWEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL) [ppm]1250 ppmRemarkCarc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))</utv>	WEL TWA (OEL TWA) [1]	1210 mg/m³		
WEL STEL (OEL STEL) [ppm]       1500 ppm         Regulatory reference       EH40/2005 (Fourth edition, 2020). HSE         HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) (68476-85-7)	WEL TWA (OEL TWA) [2]	500 ppm		
Regulatory referenceEH40/2005 (Fourth edition, 2020). HSEHYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) (68476-85-7)United Kingdom - Occupational Exposure LimitsLocal nameLiquefied petroleum gasWEL TWA (OEL TWA) [1]1750 mg/m³WEL TWA (OEL TWA) [2]1000 ppmWEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL) [ppm]1250 ppmRemarkCarc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))	WEL STEL (OEL STEL)	3620 mg/m³		
With the term of the term of the term of te	WEL STEL (OEL STEL) [ppm]	1500 ppm		
United Kingdom - Occupational Exposure LimitsLocal nameLiquefied petroleum gasWEL TWA (OEL TWA) [1]1750 mg/m³WEL TWA (OEL TWA) [2]1000 ppmWEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL) [ppm]1250 ppmRemarkCarc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
Local nameLiquefied petroleum gasWEL TWA (OEL TWA) [1]1750 mg/m³WEL TWA (OEL TWA) [2]1000 ppmWEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL) [ppm]1250 ppmRemarkCarc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))	HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) (68476-85-7)			
WEL TWA (OEL TWA) [1]1750 mg/m³WEL TWA (OEL TWA) [2]1000 ppmWEL STEL (OEL STEL)2180 mg/m³WEL STEL (OEL STEL) [ppm]1250 ppmRemarkCarc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))	United Kingdom - Occupational Exposure Limits	United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [2]       1000 ppm         WEL STEL (OEL STEL)       2180 mg/m³         WEL STEL (OEL STEL) [ppm]       1250 ppm         Remark       Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))	Local name	Liquefied petroleum gas		
WEL STEL (OEL STEL)       2180 mg/m³         WEL STEL (OEL STEL) [ppm]       1250 ppm         Remark       Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))	WEL TWA (OEL TWA) [1]	1750 mg/m³		
WEL STEL (OEL STEL) [ppm]       1250 ppm         Remark       Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))	WEL TWA (OEL TWA) [2]	1000 ppm		
Remark       Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))	WEL STEL (OEL STEL)	2180 mg/m <sup>3</sup>		
contains more than 0.1% of buta-1,3-diene))	WEL STEL (OEL STEL) [ppm]	1250 ppm		
Regulatory reference         EH40/2005 (Fourth edition, 2020). HSE	Remark			
	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		

### 8.1.2. Recommended monitoring procedures

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

No additional information available

#### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

**Eye protection:** Chemical goggles or safety glasses

#### 8.2.2.2. Skin protection

Skin and body protection: Wear suitable protective clothing

## Hand protection:

Wear protective gloves. Nitrile rubber gloves

#### 8.2.2.3. Respiratory protection

Respiratory protection: In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN140 with Type A filter or better

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### Other information:

Do not eat, drink or smoke during use.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state :	Liquid
Colour	Black
Odour :	Characteristic odour.
Odour threshold :	Not available
Melting point :	Not available
Freezing point :	Not available
Boiling point :	< 0 °C
Flammability :	Non flammable, Extremely flammable aerosol.
Explosive limits :	Not available
Lower explosion limit :	Not available
Upper explosion limit :	Not available
Flash point :	< 100 °C

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Auto-ignition temperature	: > 200 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: <1
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

9.2.1. Information with regard to physical hazard classes		
% of flammable ingredients	: 78.6009758903 %	
9.2.2. Other safety characteristics		

VOC content : 511 g/l

SECTION 10: Stability and reactivity
10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

**10.6. Hazardous decomposition products** 

fume. Carbon monoxide. Carbon dioxide.

# **SECTION 11: Toxicological information**

Acute toxicity (dermal)	Not classified Not classified Not classified		
CALCIUM CARBONATE (1317-65-3)			
LD50 oral rat	> 2000 mg/kg		
HYDROCARBONS C7-C9, ISOALKANES (6474	1-66-8)		
LD50 oral rat	7100 – 7800 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)		
LD50 dermal rabbit	2200 – 2500 mg/kg bodyweight Animal: rabbit		

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ACETONE (67-64-1)			
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female		
LD50 dermal rat 15800 mg/kg			
LC50 Inhalation - Rat	76 mg/l/4h		
HYDROCARBON AEROSOL PROPELLANT (<	D.1% 1,3-BUTADIENE) (68476-85-7)		
LC50 Inhalation - Rat	> 20 mg/l/4h		
Skin corrosion/irritation : Causes skin irritation.			
erious eye damage/irritation : Not classified			
Additional information : Respiratory or skin sensitisation :	Based on available data, the classification criteria are not met Not classified		
	Based on available data, the classification criteria are not met		
Germ cell mutagenicity :	Not classified		
Additional information :	Based on available data, the classification criteria are not met		
5 ,	Not classified		
Additional information :	Based on available data, the classification criteria are not met		
TALC (14807-96-6)			
IARC group	3 - Not classifiable,2B - Possibly carcinogenic to humans		
1 5	Not classified Based on available data, the classification criteria are not met		
ACETONE (67-64-1)			
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female		
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)		
STOT-single exposure : May cause drowsiness or dizziness.			
HYDROCARBONS C7-C9, ISOALKANES (64741-66-8)			
STOT-single exposure	May cause drowsiness or dizziness.		
ACETONE (67-64-1)			
STOT-single exposure	May cause drowsiness or dizziness.		
	Not classified Based on available data, the classification criteria are not met		
HYDROCARBONS C7-C9, ISOALKANES (6474	1-66-8)		
NOAEC (inhalation, rat, vapour, 90 days)	24.3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)		
•	Not classified		
Additional information :	Based on available data, the classification criteria are not met		
TUFGEAR Spray			
Vaporizer	Aerosol		
HYDROCARBONS C7-C9, ISOALKANES (64741-66-8)			
Viscosity, kinematic	0.6 mm²/s at 40°C		
Hydrocarbon	Yes		
11.2. Information on other hazards			
11.2.1 Endocrine disrupting properties			

### 11.2.1. Endocrine disrupting properties

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 11.2.2. Other information

Potential adverse human health effects and symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information			
12.1. Toxicity			
Ecology - water       : Harmful to aquatic life with long lasting effects.         Hazardous to the aquatic environment, short-term       : Not classified         (acute)       :         Hazardous to the aquatic environment, long-term       : Harmful to aquatic life with long lasting effects.         (chronic)       :			
CALCIUM CARBONATE (1317-65-3)			
LC50 - Fish [1]	> 100 g/l		
EC50 - Other aquatic organisms [1]	> 100 mg/l		
HYDROCARBONS C7-C9, ISOALKANES (6474	1-66-8)		
EC50 - Crustacea [1]	2.4 mg/l		
EC50 - Other aquatic organisms [1]	2.4 mg/l		
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
ACETONE (67-64-1)			
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
12.2. Persistence and degradability			
TUFGEAR Spray			
Persistence and degradability	May cause long-term adverse effects in the environment.		
12.3. Bioaccumulative potential			
TUFGEAR Spray			
Bioaccumulative potential	Not established.		
12.4. Mobility in soil			
No additional information available			
12.5. Results of PBT and vPvB assessment			
No additional information available			
12.6. Endocrine disrupting properties			
No additional information available			
12.7. Other adverse effects	12.7. Other adverse effects		
Additional information :	Avoid release to the environment.		

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations	;
13.1. Waste treatment methods	
Product/Packaging disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information Ecology - waste materials	<ul><li>Flammable vapours may accumulate in the container.</li><li>Avoid release to the environment.</li></ul>

# SECTION 14: Transport information

N 1950         UN 1950         UN 1950           s, flammable         AEROSOLS         AEROSOLS           50 Aerosols, mable, 2.1         UN 1950 AEROSOLS, 2.1         UN 1950 AEROSOLS           2.1         2.1         2.1         2.1				
s, flammable AEROSOLS AEROSOLS 50 Aerosols, nable, 2.1 UN 1950 AEROSOLS, 2.1 UN 1950 AEROSOLS				
50 Aerosols, UN 1950 AEROSOLS, 2.1 UN 1950 AEROSOLS nable, 2.1				
50 Aerosols, UN 1950 AEROSOLS, 2.1 UN 1950 AEROSOLS nable, 2.1				
nable, 2.1				
nable, 2.1				
2.1 2.1 2.1				
2.1 2.1 2.1				
14.4. Packing group				
applicable Not applicable Not applicable				
rous for the Dangerous for the Dangerous for the onment: No environment: No environment: No				
1				

## 14.6. Special precautions for user

### **Overland transport**

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 11
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading	: CV9, CV12
and handling (ADR)	
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## Transport by sea

Transport by sea		
Special provisions (IMDG)	:	63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	:	P207, LP200
Special packing provisions (IMDG)	:	PP87, L2
EmS-No. (Fire)	:	F-D
EmS-No. (Spillage)	:	S-U
Stowage category (IMDG)	÷	None
Stowage and handling (IMDG)		SW1, SW22
Segregation (IMDG)		SG69
	•	
Air transport		
PCA Excepted quantities (IATA)		E0
PCA Limited quantities (IATA)		Y203
PCA limited quantity max net quantity (IATA)		30kgG
PCA packing instructions (IATA)		203
PCA max net quantity (IATA)		75kg
,		203
CAO packing instructions (IATA)		
CAO max net quantity (IATA)		150kg
Special provisions (IATA)		A145, A167, A802
ERG code (IATA)	:	10L
Inland waterway transport		
Classification code (ADN)		5F
Special provisions (ADN)		190, 327, 344, 625
Limited quantities (ADN)		1 L
Excepted quantities (ADN)		EO
Equipment required (ADN)		PP, EX, A
Ventilation (ADN)		VE01, VE04
Number of blue cones/lights (ADN)	:	1
Rail transport		
Classification code (RID)		5F
Special provisions (RID)		190, 327, 344, 625 1L
Limited quantities (RID)		
Excepted quantities (RID)		E0
Packing instructions (RID)		P207, LP200
Special packing provisions (RID)		PP87, RR6, L2
Mixed packing provisions (RID)		MP9
Transport category (RID)		2
Special provisions for carriage – Packages (RID)		W14
Special provisions for carriage - Loading, unloading	:	CW9, CW12
and handling (RID)		
Colis express (express parcels) (RID)	:	CE2
Hazard identification number (RID)	:	23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

#### **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### VOC Directive (2004/42)

VOC content

: 511 g/l

#### **Explosives Precursors Regulation (2019/1148)**

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors) ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name		Nomenclature	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code	
Acetone	67-64-1	2914 11 00	ex 3824 99 92	

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list\_of\_competent\_authorities\_and\_national\_contact\_points\_en.pdf

#### **Drug Precursors Regulation (273/2004)**

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

#### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information	
Data sources	REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information	: None.

Full text of H- and EUI	Ill text of H- and EUH-statements:		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2		
Asp. Tox. 1	Aspiration hazard, Category 1		
Carc. Not classified	Carcinogenicity Not classified		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Gas 1A	Flammable gases, Category 1A		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. Not classified	Flammable liquids Not classified		

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Muta. Not classified	Germ cell mutagenicity Not classified	
Press. Gas (Comp.)	Gases under pressure : Compressed gas	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.