

PRODUCT INFORMATION



# **Duster 45 Spray**

# Powerful, non-abrasive, microscopic dust particles remover

# **Product description**

High purity moisture free high pressure cleaning agent

# **Applications**

Use on all equipment to remove dust in any industrial, marine, aviation electrical/electronic equipment as:

- Photographic equipment
- Watch mechanisms
- Film negatives
- Computers
- Data processing equipment
- Electromechanical instruments
- Printed circuit boards
- Fiber glass connectors
- Communication equipment
- Precision equipment

### Features & benefits

- Delivers pure 100% dry, moisture free cleaning agent
- Non-conductive and safe to use on all metals, plastics, rubbers, optics, glass and delicate components
- Non staining & noncorrosive
- Leaves no residue and blows away microscopic dust, lint, sand, metallic oxides and other soils

### How to use

Do not shake can before or during use and hold can upright while spraying. Clear any liquid residue that may have formed in the dip tube of the valve stem by pressing the actuator. Use short blast spray method. Use extension tube for tight areas. Spray on film negatives only after clearing the valve first. DO NOT SPRAY ON SKIN AS IT MAY CAUSE FROSTBITE.

### Caution

Contains flammable propellant and solvents. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.



### PRODUCT INFORMATION



Test	Unit	Result
Appearance		Hydrocarbon gas propelled liquid
Description		Pressurized liquid
Colour		Colourless
Odor		Mild
Film type		Gas
Specific gravity concentrate	g/cm <sup>3</sup>	0.53-0.55
ISO VG grade		N/A
Evaporation rate		N/A
KB value		N/A
Dielectric strength		N/A
Plastic safe		Yes
Service temperature range	°C	N/A
Flash point	°C	-25°C (closed cup) aerosol
Flammability class		Extremely flammable
Film thickness	Mils	N/A
Dry time, full dry	h	N/A
Dry time, tack free	h	N/A
Recoat	h	N/A
Method of removal		N/A
Four ball weld load	N	N/A
Four ball wear	mm	N/A
NSF category code		N/A
NSF number		N/A
Solubility in water		No
Coverage	m²/can	N/A
Propellant		Hydrocarbon
Shelf life	months	36 from date of manufacture
		N/A: not applicable

N/A: not applicable

## General

Use in well-ventilated areas. Avoid continuous breathing of vapor and spray mist. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

## Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards.

Manufactured by: ASV Multichemie Private Limited E 14, Additional MIDC, Patalganga Panvel-410 220 INDIA



# **Disposal**

All used and unused product should be disposed of in accordance with state

# **Limited warranty**

Product manufactured is for industrial use only. The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK® SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV MULTICHEMIE PRIVATE LIMITED, INDIA