

Technical Data Sheet

SC2000 CEMENT

TDS #: RTTNA – 033 Rev. # 1

Rev. Date: 1/14/2014

PRODUCT NUMBERS: 101 000 041, 101 000 042, 101 000 043

CONTAINERS/PACKAGING: 101 000 041 - ½ KG Can 101 000 042 - 1 KG Can 101 000 043 – 5 KG Can

FIELD OF APPLICATION: Rema's SC2000 Cement is applicable for durable rubber-to-metal, rubber-to-rubber, rubber-to-fabric, and fabric-to-fabric bonding in the fields of wear and corrosion protection, as well as in conveyor belt technology.

| PRODUCT ADVANTAGES: | Excellent contact adhesion (green tack) |
|----------------------------|--|
| | Non-Flammable |
| | Approved for use in underground applications |
| | Optimum adhesion when used with Rema Tip Top primers and |
| | cleaning fluids |
| | Easily processed, even at low temperatures |
| | Provides superior bonds at room temperature when processed with Rema Hardener UT-R 20 |
| | Long shelf life when stored as recommended |
| | Available in Black and white colors |
| | |
| | |

PHYSICAL PROPERTIES: Flash Point = > 200° F (> 93° C) Tag Closed Cup Density = 12.1 Lbs./Gallon (Typical) Boiling Point = Approximately 194° F (93° C) Relative Vapor Density = 4.54 (Air = 1) Solids Content = 14.0 – 19.0 (Typical) Viscosity = 2000 – 3600 cps @ 70° F (21° C) (Typical) VOC Content = 11.0 Lbs./Gallon (Typical)

INSTRUCTIONS FOR USE: Per the manufacturer's instructions. Rema Tip Top will provide detailed instruction for your intended use upon request.



Technical Data Sheet

SC2000 CEMENT

| TDS #: RTTNA – 033 F | Rev. # 1 | Rev. Date: 1/14/2014 |
|--|--|--|
| SAFETY INSTRUCTIONS | Skin and eye irritant. May cause cancer. May cause damage to Central Nerve May cause damage to organs with p Use only in a well-ventilated area. See Safety Data Sheets for more det measures. | prolonged or repeated exposure |
| SHELF LIFE: | 4 Years from Date of Manufacture i | in unopened original container. |
| BASE SOLVENT: | Trichloroethylene (CAS# 79-01-6) | |
| RECOMMENDED STORA CONDITIONS: | GE Store in a cool, well-ventilated, dry of Keep away from open flames, ignition materials (See Safety Data Sheet for Keep container tightly closed. Keep away from food, drink, and an | on sources, and incompatible for details). |

NOTICE: REMA TIP TOP / NORTH AMERICA believes that the information contained on this data sheet is accurate. It is based on extensive tests and represents standard values. However, it may not contain information on all confirmed properties. REMA TIP TOP / North America reserves the right to carry out improvements and technical development to this product at its discretion. For detailed application instructions, always refer to the appropriate Rema Tip Top Instruction Manuals and/or Repair Instruction CD's. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive, nor fully adequate in every circumstance. Also, the suggestions should not be confused with nor followed in violation of applicable laws, regulations, rules or insurance requirements.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.