

## V & V (MF) Powder

### Highly refined & pure MoS<sup>2</sup> powder

#### Features & benefits

- Extremely wide service temperature range of -185°C to +450°C
- Very good affinity to metal surfaces
- High surface pressure carrying capacity
- Reduces wear and friction
- Does not attract or accumulate dust and dirt
- Very low coefficient of friction
- Very effective for lubrication under vacuum and radioactive conditions
- Chemically inert and resistant to solvents, steam, heat and liquid oxygen

#### Applications

- For effective break in or running in of components to prevent excessive wear, friction, galling, seizure of newly assembled machined surfaces.
- As a press fitting lubricant to avoid distortion, misalignment, seizure, galling and reduce pressures required. Makes assembly easy and disassembly non-destructive.
- For preventing cold welding and fretting under static loads.
- For extending wear life of metal components.
- For lubrication of sliding surfaces under slow speeds and heavy loads where an oil film cannot be maintained.
- As a metal release agent for preventing sticking of material during casting.
- As a metal forming lubricant to prevent galling, metal pick up, reduce friction and heat and increase wear life of tools and dies in machining, stamping, cold forming, thread cutting operations.
- As a pretreatment to all sliding surfaces to prevent excessive wear and provide lubrication under vibration and shock loads.
- For lubrication of components exposed to extreme environments as liquid or gaseous oxygen, radiation, and vacuum.
- As an extreme pressure additive to lubricating oils and greases to reduce friction and wear.
- For incorporation and impregnation into plastics, rubbers, metals for low frictional properties as for plastic bearings, rods, bushes, gears, O-rings, seals.

#### How to use

For optimum performance, clean the contact surface.

Use any ASV heavy duty industrial strength solvent based cleaner degreaser available in aerosol spray or bulk liquid pack.

When using a water based degreaser, ensure complete removal of any residues of the water based alkaline cleaning solution prior to applying grease.

Apply on clean, dry, degreased contact points by tumbling, burnishing, rubbing or polishing on the surface. Rub intensively on the metal surface to form a thin uniform lubricating film.

Test	Result
Type	Powder
Appearance	Free flowing, lump free micro fine solid particles
Color	Gray black
Density, g/cc	4.8
Purity	98.5 %
Average particle size, µ	V Powder = 2.5 – 5 V(MF) Powder = 1.5-3.5
Magnetic properties	Nonmagnetic
Load bearing capacity	Exceeds yield point of most known metals
Special properties	<ul style="list-style-type: none"><li>▪ Lubricates under pressures exceeding 500,000 psi.</li><li>▪ Unaffected by liquid oxygen, vacuum and suitable for use near radioactive areas.</li><li>▪ Nonconductive</li></ul> Confirms to Military specifications MIL-M-7866
Service temperature range, °C	-185 to +450 under normal conditions (up to +1100 under vacuum conditions)

## General

Use in well-ventilated areas. Avoid continuous breathing of vapor and spray mist. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

## Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards.

Manufactured by:  
ASV Multichemie Private Limited  
E 14, Additional MIDC, Patalganga  
Panvel-410 220 INDIA



**WWW.ASVMULTICHEMIE.COM**

## Disposal

All used and unused product should be disposed of in accordance with state regulations.

## Limited warranty

Product manufactured is for industrial use only. The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK®  
SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV  
MULTICHEMIE PRIVATE LIMITED, INDIA