

Belt Dressing Spray

Anti slip & belt conditioning agent; NSF registered

Product description

- Synthetic lubricant for belts

Applications

For use on all round, flat & V-belts in fans, pumps, machines, conveyors, air conditioners, textile machines, compressors, generators in all industrial machinery, conveyor systems, motorized equipment and vehicles. Not to be used on timing or serpentine belts.

Features & benefits

- NSF registered for food grade applications
- Eliminates belt squeaking or squealing noises
- Provides for better operating efficiency
- Prevents hardening, glazing and premature cracking
- Increases life and tensile strength of belts
- Reduces energy loss through effective power transfer
- Maintains flexibility and resilience of belts

How to use

Switch off the power and turn off the equipment before spraying this product. Protective guards or covers may have to be removed in some instances. Replace guards after application. Spray from a distance of 6-8 inches a light, even film on the stationary inner surface of belt in contact with pulleys from both the sides. Spray enough only to cover the length of the belt. Allow few minutes for the solvents to evaporate before restarting the equipment. Reapply occasionally to maintain full power and to optimize belt life.

Caution

Contains flammable solvents and propellant. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.

Test	Unit	Result
Appearance		Hydrocarbon gas propelled liquid
Description		Synthetic lubricant
Colour		Colourless
Odor		Mild
Film type		Adhesive; oily
Specific gravity concentrate	g/cm ³	0.65-0.67
ISO VG grade		N/A
Evaporation rate		N/A
KB value		N/A
Dielectric strength		N/A
Plastic safe		Yes
Service temperature range	°C	N/A
Flash point	°C	-25°C (closed cup) aerosol
Flammability class		Extremely flammable
Film thickness	Mils	N/A
Dry time, full dry	h	N/A
Dry time, tack free	h	N/A
Recoat	h	N/A
Method of removal		N/A
Four ball weld load	N	N/A
Four ball wear	mm	N/A
NSF category code		H1
NSF number		Registration certificate # 168931
Solubility in water		No
Coverage	m ² /can	N/A
Propellant		Hydrocarbon
Shelf life	months	36 from date of manufacture

N/A: not applicable

General

Use in well-ventilated areas. Avoid continuous breathing of vapor and spray mist. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards.

Manufactured by:
ASV Multichemie Private Limited
E 14, Additional MIDC, Patalganga
Panvel-410 220 INDIA



WWW.ASVMULTICHEMIE.COM

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Limited warranty

Product manufactured is for industrial use only. The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK®
SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV
MULTICHEMIE PRIVATE LIMITED, INDIA