

PTFE-Spray



grease-free excellent sliding properties (non-stick)

WEICON PTFE-Spray is a grease-free PTFE-based dry lubricant with excellent sliding properties. WEICON PTFE Spray adheres to all metal, plastic and wood surfaces. Its high PTFE content greatly reduces the friction coeffi cient. The coating repels dirt, dust and water and is resistant to oils, greases and many chemicals.

PTFE Spray can be used on runners and guides, conveyor belts, transport rollers, slides, windows, cutting tools and packing machines. It can also be used as a permanent lubricant for shafts in plastic bearings, as a water-rejecting coating for paper seals, cork seals and seal packaging, as a substitute for release agents containing silicone, and wherever oil or grease lubrication is not permitted or desired. The product can be used in many industrial applications.

Technical Data

Odour	almost odourless
Features	PTFE basis
Silicone free	yes
Storage stability	24 months
Colour	white
Temperature resistance	-180 to +250 °C
ISSA-Code	53.402.13
IMPA-Code	450827

Processing

Clean and degrease surfaces prior to application. Shake can until rattle of mixing ball is heard. Spray on cleaned and dry surfaces from about 20 cm distance. In case of continued use, shake can again from time to time. At room temperature (+20°C), the coating is dust-dry approx. 10 minutes after spraying.

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG (Headquarters) Germany phone +49 (0) 251 9322 0 info@weicon.de www.weicon.de

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za www.weicon.co.za WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae www.weicon.ae

WEICON South East Asia Pte Ltd Singapore phone (+65) 6710 7671 info@weicon.com.sg www.weicon.com.sg WEICON Inc. Canada phone +1 877 620 8889 info@weicon.ca www.weicon.ca

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weicon.cz www.weicon.cz WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr www.weicon.com.tr

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es www.weicon.es WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@weicon.com www.weicon.com.ro

WEICON Italia S.r.I. Italy phone (+39) 0102924871 info@weicon.it www.weicon.it

Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding $+50^{\circ}$ C.

Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes:

11300400

PTFE-Spray 400 ml