

A116 Liquid Grease

Description

Akfix 116 is a multi-purpose sprayable lubricant grease designed with excellent adhesion, compressive strength and antiwear properties.

Properties & Features

- Excellent and permanent lubrication,
- Excellent adhesion,
- Rust prevention,
- Water resistant,
- Vibrating parts lubricating,
- Silicone and acid-free,
- Ability to lubricate difficult to reach areas,
- Provides superior lubrication with wear, anti-friction and protection additives.

Fields of Application

Especially at forklift chains, motorcycle chains, open gears, chain and wire ropes, moving parts, mechanical parts in need of open use and lubrication. Relays, bearings, ball bearings, auto door hinges, clutch and brake bars, motor vehicles, garden and agricultural tools. At industrial and maritime applications.

Product Information

Packaging	500 ml
Shelf Life	24 months
Storage	At cool and dry ambient

Technical Data

Parameter	Value
Color	Yellowish
Density	0,829 g/cm ³
Flammability Temperature	>200°C
Odor	Characteristic

Directions for Use

- Clean the parts to be lubricated thoroughly,
- Shake the can well before use,
- Spray the product from a distance of 25-30 cm to the surface to be lubricated

Remark & Restrictions

- The can is pressurized. Protect from sunlight.
- Do not smoke during operation and ventilate the area.

Safety

Ensure good ventilation of the work station. Wear personal protective equipment. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Store in a well-ventilated place. Keep cool. Check MSDS guidelines for disposal and further information concerning safety. Keep out of reach of children.

Rev no:0001 Rev Date: 07.11.202









1 Yeşilbayır Mah. Şimşir Sk. No: 22 Arnavutköy - İstanbul / TÜRKİYE Tel: 0212 771 13 71 Fax: 0212 771 38 88 www.akfix.com - info@akfix.com







Disclaimer

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

Rev no:0001 Rev Date: 07.11.2023 **CREATES** PERMANENT

SOLUTIONS











2 Yeşilbayır Mah. Şimşir Sk. No: 22 Arnavutköy - İstanbul / TÜRKİYE Tel: 0212 771 13 71 Fax: 0212 771 38 88 www.akfix.com - info@akfix.com

