



– Yesilbayır Mah. Şimşir Sk. No: 22 Hadımköy - İstanbul/TÜRKİYE Tel: 0212 771 13 71 Fax: 0212 771 38 88 🔰 www.akfix.com - info@akfix.com

# **303 SUPER GLUE**

## **1 – DESCRIPTION**

**Akfix 303** is low viscosity superfast instant glue based on cyanoacrylate adhesive. It is excellent where extremely fast cure is required.

## **2 – PROPERTIES**

- Immediate bond
- Very high bond strength after a few seconds

## **3 - APPLICATIONS**

• Suitable for glass, rubber, metals, ceramic and many plastics.

#### **4 - INSTRUCTIONS**

Substrates need to be smooth and have a perfect connection area. Apply a drop on one of the substrates. Join substrates and press firmly for one minute. Application temperature is between  $+5^{\circ}C$  and  $+4^{\circ}C$ 

#### **5- PACKAGING**

| Product | Volume | Package |
|---------|--------|---------|
| 303     | 3 gr   | 12/144  |

#### 6- STORAGE AND SHELF LIFE

12 months in unopened original packaging when stored between +5°C and +25°

#### **7- RESTRICTIONS**

- Cyanoacrylate should ideally be stored in original sealed containers until used.
- Avoid exposure to strong light and heat sources.
- Cyanoacrylate can bond to skin within seconds.
- Do not drip into skin or into eyes can cause serious injury to your eyes.
- Will become hard in container if not closed properly!

#### **8- TECHNICAL PROPERTIES**

| Basis                   | : Ethyl Cyanoacrylate            |            |  |
|-------------------------|----------------------------------|------------|--|
| Appearance              | : Liquid gel                     |            |  |
| Color                   | : Colorless                      |            |  |
| Application Temperature | : +5°C to +35°C                  |            |  |
| Density                 | : 1.05 ± 0.01 gr/cm <sup>3</sup> | ASTM D1875 |  |
| Flashpoint              | :>81°C                           |            |  |
| Viscosity               | : 40 - 80 Cps at 25°C            | ASTM D1084 |  |