



Yeşilbayır Mah. Şimşir Sk. No: 22 Hadımköy - İstanbul/TÜRKİYE. Tel: 0212 771 13 71 Fax: 0212 771 38 88 🗴 www.akfix.com - info@akfix.com

A70 PENETRATING OIL SPRAY

1 – DESCRIPTION

AKFIX A70 is high performance penetrating oil enriched with MoS2.

2 – PROPERTIES

- Excellent penetrating capability. Penetrates into hard-to-reach areas quickly. •
- Loosen rusted parts and form a protective layer between metal surfaces.
- Diminish friction. •
- Remove water and protects against moisture. •
- Protects metal parts and surfaces from corrosion. •
- Eases quick disassembly of mechanical components, fittings, assemblies, nuts • and bolts and other close tolerance fasteners.
- Leaves a solid lubricating MoS2 film. •
- Reduces wear and facilitates future disassembly. •
- MoS2 reduces friction even elevated temperatures.

3 – APPLICATIONS

- Seized and rusted nuts and bolts •
- Locks and hinges •
- Screwed parts •
- Equipment disassembly •
- Corroded fasteners •
- Valves •
- Air tools •
- Chains and conveyors
- Agricultural equipment •

4 – INSTRUCTIONS

- Clean the surface thoroughly, degrease and make it dry. •
- Shake the can well before use. •
- Spray on approx. 20 25 cm distance from the surface.
- Allow a few minutes for penetration. •
- Repeat if necessary. •





Yeşilbayır Mah. Şimşir Sk. No: 22 Hadımköy - İstanbul/TÜRKİYE Tel: 0212 771 13 71 Fax: 0212 771 38 88 > www.akfix.com - info@akfix.com

5- PACKAGING

Product	Volume	Package
A70	200ml	24
A70	400ml	12

6- SHELF LIFE

24 Months if stored properly.

7- SAFETY

- Use gloves when working.
- Pressurized container. Do not expose to temperatures higher than +50 °C. •
- Keep away from direct sunlight •
- Do not pierce or burn, even after use. •
- Keep away from sources of ignition, no smoking. •
- Keep out of the reach of children. •

8- TECHNICAL PROPERTIES

Basis	: Solvent and oil mixture with MoS ₂
Appearance	: Black colored liquid
Specific gravity	: 0,77±0,03 gr/cm ³
Odor	: Characteristic